

FASTIN-FASTON | FASTIN-FASTON 250

TE Internal #: 282180-3

Quick Disconnects, Receptacle, 20 – 15 AWG Wire Size, .51 – 1.65 mm² Wire Size, Mating Tab Width 4.75 mm [.187 in], Straight,

FASTIN-FASTON 250

View on TE.com >



Terminals & Splices > Quick Disconnects











Quick Disconnect Terminal Type: Receptacle

Wire Size: .51 – 1.65 mm²

Mating Tab Width: 4.75 mm [.187 in]

Mating Tab Thickness: .81 mm [.032 in]

Features

Product Type Features

Insertion Force	Normal
Configuration Features	
Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire
Electrical Characteristics	
Voltage Rating	250 V
Contact Features	
Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	4.75 mm[.187 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Phosphor Bronze
Terminal Plating Material	Unplated
Crimp Type	F-Crimp



Barrel Type	Open
Termination Features	
Product Terminates To	Wire & Cable
Mechanical Attachment	
Extraction Force	4 Newton
Wire Insulation Support	With
Mating Retention Type	Locking Lance
Dimensions	
Terminal Material Thickness	.25 mm[.01 in]
Product Length	16.6 mm[.653 in]
Compatible Insulation Diameter Range	1.5 – 2.4 mm[.059 – .094 in]
Wire Size	.51 – 1.65 mm²
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]
Packaging Features	

Product Compliance

Packaging Quantity

Packaging Method

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

10000

Strip/Reel

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 2150303-1
OCEAN_2.0_Applicator-E-090F120F



TE Part # 2150303-2 OCEAN_2.0_Applicator-E-090F120F



TE Part # 7-2150303-1 OCEAN_2.0_Applicator-E-090F120F



TE Part # 7-2150303-2 OCEAN_2.0_Applicator-E-090F120F




Also in the Series | FASTIN-FASTON 250














Quick Disconnects(254)

Customers Also Bought

















Documents

Product Drawings

FF 187 REC 0.5-1.5MM2 TPPB

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_282180-3_E.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_282180-3_E.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_282180-3_E.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

1654742_HOUSEHOLD_APPLIANCES_RAST5

English

Product Specifications

Application Specification

FASTIN-FASTON Connector, .187 rec. ctc.