
# 284865-9 - ACTIVE

### RAST

TE Internal #: 284865-9 Standard Edge Connectors, Wire-to-Board, 9 Position, .098 in [2.5 mm] Centerline, Insulation Displacement (IDC), 1 Row, Black, PBT GF, Fully Loaded

### View on TE.com >

Connectors > PCB Connectors > Card Edge Connectors > Standard Edge Connectors



Connector System: Wire-to-Board

Number of Positions: 9

Centerline (Pitch): 2.5 mm [.098 in]

Termination Method to Wire & Cable: Insulation Displacement (IDC)

Number of Rows: 1

### Features

### **Product Type Features**

Connector System

Wire-to-Board

Connector & Housing Type

Connectivity

Receptacle

Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Card Entry Style	Side
Compatible With Wire & Cable Type	Discrete Wire
Number of Positions	9
Number of Rows	1
Connector Contact Load Condition	Fully Loaded
PCB Mount Orientation	Right Angle
Electrical Characteristics	
Operating Voltage	63 VAC
Body Features	
Keying Between Cavity Locations	2&3
Primary Product Color	Black
Contact Features	

**C** For support call+1 800 522 6752

Standard Edge Connectors, Wire-to-Board, 9 Position, .098 in [2.5 mm] Centerline, Insulation Displacement (IDC), 1 Row, Black, PBT GF, Fully Loaded



Contact Retention Within Housing	Without
PCB Contact Termination Area Plating Material Thickness	4 – 10 μm
Contact Type	Socket
Contact Mating Area Plating Material	Tin
Contact Base Material	Phosphor Bronze
Contact Current Rating (Max)	2 A
Termination Features	
Termination Method to Wire & Cable	Insulation Displacement (IDC)
Mechanical Attachment	
Mating Alignment Type	Keyed
Mating Retention	With
Mating Alignment	With
PCB Mount Alignment	With
PCB Mount Retention	With
Connector Mounting Type	Board Mount
Housing Features	
Housing Entry Configuration	Both Ends Closed
Centerline (Pitch)	2.5 mm[.098 in]
Housing Material	PBT GF
Dimensions	
Card Slot Depth	5 mm
Connector Height	7.35 mm
PCB Thickness (Recommended)	
	1.5 mm[.059 in]
Compatible Insulation Diameter Range	1.5 mm[.059 in] 1.3 – 2.1 mm[.05 – .08 in]
Compatible Insulation Diameter Range	1.3 – 2.1 mm[.05 – .08 in]
Compatible Insulation Diameter Range Wire Size	1.3 – 2.1 mm[.05 – .08 in]
Compatible Insulation Diameter Range Wire Size Usage Conditions	1.3 – 2.1 mm[.05 – .08 in] .22 – .35 mm <sup>2</sup>
Compatible Insulation Diameter Range Wire Size Usage Conditions Operating Temperature Range	1.3 – 2.1 mm[.05 – .08 in] .22 – .35 mm <sup>2</sup>
Compatible Insulation Diameter Range Wire Size Usage Conditions Operating Temperature Range Operation/Application	1.3 – 2.1 mm[.05 – .08 in] .22 – .35 mm <sup>2</sup> -40 – 110 °C[-40 – 230 °F]
Compatible Insulation Diameter Range Wire Size Usage Conditions Operating Temperature Range Operation/Application Circuit Application	1.3 – 2.1 mm[.05 – .08 in] .22 – .35 mm <sup>2</sup> -40 – 110 °C[-40 – 230 °F]

Standard Edge Connectors, Wire-to-Board, 9 Position, .098 in [2.5 mm] Centerline, Insulation Displacement (IDC), 1 Row, Black, PBT GF, Fully Loaded



## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.

### Solder Process Capability

Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## **Compatible Parts**



Customers Also Bought

Standard Edge Connectors, Wire-to-Board, 9 Position, .098 in [2.5 mm] Centerline, Insulation Displacement (IDC), 1 Row, Black, PBT GF, Fully Loaded







TE Part #2-284931-5 DUOPLUG Standard, female conn.

### Documents

CAD Files

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_284865-9\_B.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_284865-9\_B.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_284865-9\_B.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages 1654742\_HOUSEHOLD\_APPLIANCES\_RAST5

English

**Product Specifications** 

**C** For support call+1 800 522 6752

Standard Edge Connectors, Wire-to-Board, 9 Position, .098 in [2.5 mm] Centerline, Insulation Displacement (IDC), 1 Row, Black, PBT GF, Fully Loaded



**Application Specification** 

English

Product Environmental Compliance TE Material Declaration

English

Agency Approvals

Agency Approval Document

English