




Relays, Contactors & Switches > Relays > Power Relays > P&B SSR SLIM OUTPUT AC MODULES



Power Relay Type: **Solid State**

Contact Arrangement: **1 Form A (SPST-NO)**

Relay Mounting Type: **Printed Circuit Board**

[All P&B SSR SLIM OUTPUT AC MODULES \(4\)](#)

## Features

### Product Type Features

Output Type	AC
Power Relay Type	Solid State

### Configuration Features

Output Switching	Zero
------------------	------

### Electrical Characteristics

Input Voltage Typical	5 VDC
Output Voltage (Max)	280 V
Output Voltage Rating (AC Relays)	24 – 280 Vrms
Output Current Rating	.05 – 3 Arms
Output Current (Min)	.05 A
Insulation Initial Dielectric Between Contacts & Coil	4000 Vrms

### Body Features

Product Weight	22.1 g[.87 oz]
Case Color	Black



### Contact Features

Switch Arrangement	1 Form A (SPST-NO)
Contact Arrangement	1 Form A (SPST-NO)

### Termination Features

Relay Termination Type	Printed Circuit Terminals
------------------------	---------------------------

### Mechanical Attachment

Coupling	Optical
Relay Mounting Type	Printed Circuit Board

### Housing Features

Relay Housing Style	Slimline
---------------------	----------

### Dimensions

Dimensions (L x W x H) (Approximate)	43.6 x 10.3 x 25.5 mm[1.717 x .406 x 1.004 in]
--------------------------------------	--

### Usage Conditions

Operating Temperature Range	-30 – 80 °C
-----------------------------	-------------

### Operation/Application

R-Switch & slimSSR Relays	Yes
---------------------------	-----

## Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) SVHC > Threshold: Pb (88% in Component Part) <b>Article Safe Usage Statements:</b> Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 260°C

Product Compliance Disclaimer




This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

## Compatible Parts



TE Part # 3-1393028-8  
OACM-5 = SLIM PCB MONT,3A,  
120VAC-DC I/p

## Also in the Series | Potter & Brumfield OACM



Power Relays(3)


## Customers Also Bought




TE Part #5555141-1  
MJ,LPF,R/A,8P/8C,SHLD,PNL GRD



TE Part #205165-1  
RECEPT ASSY,25 POSN,AMPLIMITE



TE Part #2-103168-3  
50 MODII HDR DRST SHRD .100CL



TE Part #3-534998-0  
60 MODIV VRT DR CE 100/125



## Documents

### CAD Files

#### Customer View Model

[ENG\\_CVM\\_CVM\\_3-1393028-1\\_D1.3d\\_igs.zip](#)

English

#### Customer View Model

[ENG\\_CVM\\_CVM\\_3-1393028-1\\_D1.3d\\_stp.zip](#)

English

#### Customer View Model

[ENG\\_CVM\\_CVM\\_3-1393028-1\\_D1.2d\\_dxf.zip](#)

English

### 3D PDF

3D

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

### Datasheets & Catalog Pages

#### OACM Slim Line AC Output Modules Data Sheet

English

[OACM\\_Datasheet](#)

English

### Agency Approvals

[UL](#)

English