

W31-X2M1G-35 ✓ ACTIVE

Potter & Brumfield | Potter & Brumfield W23-31


TE Internal #: 3-1393247-9

Circuit Breakers, Thermal, Series Trip, Silver, Operating Voltage 240 VAC, Operating Voltage 50 VDC, 35A Current Rating, Potter & Brumfield W23-31

[View on TE.com >](#)



Relays, Contactors & Switches > Circuit Breakers



Circuit Breaker Type: **Thermal**

Circuit Function: **Series Trip**

Illuminated: **No**

Actuator Color: **Silver**

Operating Voltage: **240 VAC**

Features

Product Type Features

Circuit Breaker Style	Toggle
Illumination Type	No Light
Actuator Type	Push-Pull, Toggle
Terminal Configuration	8-32 Screws 90° to Each Other
Circuit Breaker Type	Thermal
Illuminated	No

Configuration Features

	.47 (Diameter) in
Circuit Function	Series Trip
Number of Poles	1

Electrical Characteristics

Operating Voltage	50 VDC
Current Rating	35 A
Interrupt Capacity	1000A @ 50VDC or 240VAC

Body Features

Actuator Color	Silver
----------------	--------

Contact Features

Trip Time at 200%	6 – 22 seconds
-------------------	----------------



Mechanical Attachment

Mounting Hardware Packaging	Assembled to Bushing
Mounting Bushing	15/32-32 Threaded Bushing .32" Long Double "D", Silver Color
Mounting Options	Two Hex Nuts/Lockwasher

Identification Marking

Stamped Marking Type	Amp Rate Marking
----------------------	------------------

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Cadmium oxide (10% in Component Part) Article Safe Usage Statements: Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>


Compatible Parts



Also in the Series | **Potter & Brumfield W23-31**



Customers Also Bought





Documents

CAD Files

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_3-1393247-9_C_c-3-1393247-9-c.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_3-1393247-9_C_c-3-1393247-9-c.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_3-1393247-9_C_c-3-1393247-9-c.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[W23/31 Toggle or Push/Pull Actuator Thermal Circuit Breaker](#)

English

[W23/W31 Series Datasheet](#)

English

Agency Approvals

[UL](#)

English