TE Internal #: 3-1393248-8

Circuit Breakers, Thermal, Poles 1 & 2 - Series Trip Overload Sensor, Illuminated, White, Operating Voltage 250 VAC, Operating

Voltage 50 VDC

View on TE.com >



Relays, Contactors & Switches > Circuit Breakers



Circuit Breaker Type: Thermal

Circuit Function: Poles 1 & 2 - Series Trip Overload Sensor

Illuminated: Yes

Actuator Color: White

Operating Voltage: 250 VAC

Features

Product Type Features

Circuit Breaker Style	Power Switch
Illumination Type	No Light
Actuator Type	Rocker
Terminal Configuration	6.35 [.25] Straight Quick Connect Tab
Circuit Breaker Type	Thermal
Illuminated	Yes

Configuration Features

Panel Cutout Size	22.22 x 44.45 mm
Circuit Function	Poles 1 & 2 - Series Trip Overload Sensor
Number of Poles	2

Electrical Characteristics

Operating Voltage	50 VDC
Current Rating	15 A
Interrupt Capacity	1000A @ 50VDC/250VAC or 1500A @ 125 /250VAC

Body Features

Actuator Color	White	
----------------	-------	--

Contact Features

Trip Time at 200%	3 – 33 seconds
·	



Mechanical Attachment

Mounting Options	Snap-In Panel Mount
Dimensions	
Panel Thickness (Recommended)	.81 – 6.35 mm[.032 – .25 in]
Identification Marking	
Stamped Marking Type	International I/O

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2022 (224) SVHC > Threshold: Cadmium oxide (3.76% in Component) Pb (3.33% in Component) Article Safe Usage Statements: Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





TE Part # 2-1393248-6 W33-S4B1Q-15=W33



TE Part # 1393248-7 W33-S1N1Q-15=W33



TE Part # 3-1393248-9 W33-T2N1Q-20=W33





TE Part # 3-1393248-3 W33-T1N1Q-15=W33



TE Part # 2-1393248-2 W33-S3B1Q-15=W33

Customers Also Bought



TE Part #5747150-8



TE Part #6609007-3



TE Part #1-1609034-9



TE Part #5745783-2 25 MSFL RCPT RA 318 (FM)



TE Part #2-6609104-9 PE0S0DSXB=C1302



TE Part #350690-2 UMNL PIN 24-18 AUBR L/P



TE Part #1-2176345-9 CRGCQ 1210 330R 1%



RECP ASSY

TE Part #11103612-00 1500 PSI, 1/8MNPT, 0.25-5V, Cable, 2ft.,

Documents

Circuit Breakers, Thermal, Poles 1 & 2 - Series Trip Overload Sensor, Illuminated, White, Operating Voltage 250 VAC, Operating Voltage 50 VDC



CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_3-1393248-8_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_3-1393248-8_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_3-1393248-8_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

W33 Series

English

W33 One- and Two-Pole, Switchable Thermal Circuit Breaker / Power Switch With Optional Indicator Lamp

English