3-1415001-2 <

Power Relay F TE Internal #: 3-1415001-2 Maxi Relays, 12 VDC Coil Voltage, Plug-In, Monostable, DC, 90 Ω Coil Resistance, Power Relay F

View on TE.com >



Relays, Contactors & Switches > Relays > Automotive Relays > Automotive Plug-In Relays > Maxi Relays



Rated Coil Voltage: 12 VDCMaxi Relay Contact Current Class: >50AMaxi Relay Mounting Type: Plug-InMaxi Relay Coil Magnetic System: Monostable, DCMaxi Relay Coil Resistance: 90 Ω

Features

Product Type Features

	Relay Туре	Power Relay F7
Electrical Characteristics		
	Coil Power Rating Class	>1.5W
	Current Rating (85°C)	70 A

5.	'	

Contact Limiting Short-Time Current	300 A	
Insulation Initial Dielectric Between Contacts and Coil	500 Vrms	
Insulation Initial Dielectric Between Coil/Contact Class	0 – 500 V	
Coil Power Rating (DC)	1600 mW	
Insulation Initial Dielectric Between Open Contacts	500 Vrms	
Contact Limiting Making Current	240 A	
Contact Limiting Continuous Current	70 A	
Rated Voltage	12 VDC	
Contact Limiting Breaking Current	70 A	
Contact Switching Load (Min)	1000mA @ 5VDC	
Rated Coil Voltage	12 VDC	
Maxi Relay Coil Magnetic System	Monostable, DC	
Maxi Relay Coil Resistance	90 Ω	
Body Features		
Weight	38 g[1.3 oz]	

3-1415001-2

Maxi Relays, 12 VDC Coil Voltage, Plug-In, Monostable, DC, 90 Ω Coil Resistance, Power Relay F



Contact Features

Terminal Type	PCB-THT	
Contact Arrangement	1 Form A (NO)	
Contact Base Material	Silver Alloy	
Maxi Relay Contact Current Class	>50A	
Mechanical Attachment		
Maxi Relay Mounting Type	Plug-In	
Dimensions		
Width Class (Mechanical)	25 – 30 mm	
Length Class (Mechanical)	25 – 30 mm	
Height Class (Mechanical)	20 – 25 mm	
Width	25.9 mm[1.019 in]	
Length	25.9 mm[1.019 in]	
Height	24.9 mm[.98 in]	
Usage Conditions		
Environmental Ambient Temperature (Max)	125 °C[257 °F]	
Environmental Ambient Temperature Class	105 – 125°C	

Other

Mounting	Brackets
----------	----------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

3-1415001-2


Maxi Relays, 12 VDC Coil Voltage, Plug-In, Monostable, DC, 90 Ω Coil Resistance, Power Relay F



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | Power Relay F



Customers Also Bought



3-1415001-2

Maxi Relays, 12 VDC Coil Voltage, Plug-In, Monostable, DC, 90 Ω Coil Resistance, Power Relay F





Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_3-1415001-2_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_3-1415001-2_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_3-1415001-2_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use

Datasheets & Catalog Pages

Automotive Relay Application Notes

English

Power Relay F7, Maxi ISO, Plug-In

English

Product Specifications Definitions General Purpose Relays

English