3-2273124-2 - ACTIVE

TE Internal #: 3-2273124-2 M8 to M12 Cable Assembly, 3 Position, .6 m, Sensor/Actuator, Code A, M8 Plug, M12 Socket, Double Ended, Plastic View on TE.com >



Cable Assemblies > Copper Cable Assemblies > M8/M12 Cable Assemblies > M8 Male Straight to Female LED Double Ended Cable



M8/M12 Application Type: Sensor/Actuator

Number of Positions: 3

Connector & Keying Code: A

Connector Type (End A): M8 Plug

Connector Type (End B): M12 Socket

All M8 Male Straight to Female LED Double Ended Cable (20)

Features

Product Type Features

Connector Type (End A)

Connector Type (End B)

M8 Plug

M12 Socket

| Cable Assembly Type | M8 to M12 |
|------------------------------|--------------------|
| Configuration Features | |
| Status Indicator Type | LED |
| Number of Positions | 3 |
| Electrical Characteristics | |
| Operating Voltage | 24 VDC |
| Body Features | |
| Cable Color | Black |
| Connector Color (End B) | Black |
| Connector Color (End A) | Black |
| Jacket Material | PUR |
| Wire Color (Base) | Brown, Blue, Black |
| Connector & Keying Code | A |
| Contact Features | |
| Contact Current Rating (Max) | 4 A |

3-2273124-2

M8 to M12 Cable Assembly, 3 Position, .6 m, Sensor/Actuator, Code A, M8 Plug, M12 Socket, Double Ended, Plastic



Mechanical Attachment

| Thread Size | $M8 \times M8$ |
|-------------------------------|---------------------------|
| Connector Orientation (End A) | Right Angle |
| Connector Orientation (End B) | Straight |
| Housing Features | |
| Housing Material | Plastic |
| Dimensions | |
| Outside Cable Diameter | 4.1 mm[.161 in] |
| Wire Size | .326 mm ² |
| Usage Conditions | |
| Operating Temperature Range | -40 - 90 °C[-40 - 194 °F] |
| Operation/Application | |
| M8/M12 Application Type | Sensor/Actuator |
| Shielded | No |
| Packaging Features | |
| Packaging Quantity | 25 |
| Packaging Method | Box |

r deitaging method

Other

| Field Serviceable | Yes |
|------------------------------|--------------|
| Cable Assembly Length | .6 m |
| Cable Assembly Configuration | Double Ended |

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant |
|---|--|
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC |
| Halogen Content | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC |

C For support call+1 800 522 6752

3-2273124-2

M8 to M12 Cable Assembly, 3 Position, .6 m, Sensor/Actuator, Code A, M8 Plug, M12 Socket, Double Ended, Plastic



Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # T4051220003-001 M8 CABLE RA MALE 0.5M 3P PUR CABLE

Customers Also Bought



Documents

Product Drawings M8 angled scket to M8 strght plug 2 LED

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_3-2273124-2_A.2d_dxf.zip

3-2273124-2

M8 to M12 Cable Assembly, 3 Position, .6 m, Sensor/Actuator, Code A, M8 Plug, M12 Socket, Double Ended, Plastic



English

Customer View Model ENG_CVM_CVM_3-2273124-2_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_3-2273124-2_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages M8 / M12 Connector System Catalog English M8 / M12 Connector System Catalog Japanese

Product Specifications Product Specification

English