3-2316510-1 × OBSOLETE

LUMAWISE | LUMAWISE LED Holders

TE Internal #: 3-2316510-1 TE Internal Description: LUMAWISE DRIVE Z50, 0-10V, 1.05A, 24X24 LUMAWISE Drive Type Z50: Dimmable Series

View on TE.com >

Connectors > Lighting Connectors > LED Holders > LUMAWISE Drive Type Z50: Dimmable Series



Compatible LED: Bridgelux V18, Soleriq19 series

Lighting Connector Features Included: Dimmable (Linear Profile), Driver on Board, Enables Zhaga Compatibility, Not

Programmable, Optic Compatible, Thermal Protection

Operating Voltage: 48 VDC

Termination Method to Wire & Cable: Mini CT Connector

Connector System: Wire-to-Device

All LUMAWISE Drive Type Z50: Dimmable Series (0)



Features

Product Type Features

LED Holders Product Type	LED Holder
COB Substrate Thickness	1 mm
Connector System	Wire-to-Device
Configuration Features	
Lighting Connector Features Included	Dimmable (Linear Profile), Driver on Board, Enables Zhaga Compatibility, Not Programmable, Optic Compatible, Thermal Protection
Number of Positions	2
Electrical Characteristics	
Operating Voltage	48 VDC
Body Features	
Compatible LED	Bridgelux V18, Soleriq19 series

C For support call+1 800 522 6752

3-2316510-1

LUMAWISE DRIVE Z50, 0-10V, 1.05A, 24X24



Contact Features

Contact Mating Area Plating Material	Gold
Contact Base Material	Copper Alloy
Termination Features	
Termination Method to Wire & Cable	Mini CT Connector
Housing Features	
Housing Material	PBT
Usage Conditions	
Operating Temperature Range	0-125 °C[32-257 °F]
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2023 (233) Candidate List Declared Against: JUL 2017

(174) SVHC > Threshold: Not Yet Reviewed

Not Yet Reviewed for halogen content

Not reviewed for solder process capability

Halogen Content


Solder Process Capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.








Customers Also Bought





Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_3-2316510-1_1.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_3-2316510-1_1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_3-2316510-1_1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

C For support call+1 800 522 6752

3-2316510-1

LUMAWISE DRIVE Z50, 0-10V, 1.05A, 24X24



LUMAWISE Drive LED Holder Type Z50 Presentation

English

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English