LEAVYSEAL

TE Internal #: 3-2331102-1

PCB Mount Header, Vertical, Wire-to-Board, 46 Position, 4 mm Centerline, Fully Shrouded, Silver, Through Hole - Solder, Sealable,

Signal, LEAVYSEAL

View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles











Connector System: Wire-to-Board

Number of Positions: 46
Centerline (Pitch): 4 mm

Sealable: Yes

PCB Mount Orientation: Vertical

Features

Product Type Features

Troduct Type realures	
Connector Shape	Rectangular
PCB Connector Assembly Type	PCB Mount Header
Header Type	Fully Shrouded
Connector System	Wire-to-Board
Sealable	Yes
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	46
PCB Mount Orientation	Vertical
Number of Rows	3
Body Features	
Primary Product Color	Blue

 C

Connector & Keying Code



Contact Size	1.5mm
Contact Type	Tab
Mating Tab Width	1.5 mm
Mating Tab Thickness	.64 mm
Contact Mating Area Plating Material	Silver
Contact Current Rating (Max)	23 A
Termination Features	
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
Mating Alignment	With
Mating Alignment Connector Mounting Type	With Board Mount
Connector Mounting Type	
Connector Mounting Type Housing Features	Board Mount
Connector Mounting Type Housing Features Centerline (Pitch)	Board Mount

Product Compliance

Circuit Application

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Signal

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | LEAVYSEAL



Automotive Connector Caps & Covers (17)



Automotive Housings(79)



Insertion & Extraction Tools(5)



Other Automotive Connector Accessories(15)



Customers Also Bought

PCB Mount Header, Vertical, Wire-to-Board, 46 Position, 4 mm Centerline, Fully Shrouded, Silver, Through Hole - Solder, Sealable, Signal, LEAVYSEAL

















TE Part #9D-BBK-S-001S-000 0.15PSID, mV, DUAL HORIZONTAL, STICKS





Documents

Product Drawings
TAB HEADER 46POS.

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_3-2331102-1_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_3-2331102-1_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_3-2331102-1_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

PCB Mount Header, Vertical, Wire-to-Board, 46 Position, 4 mm Centerline, Fully Shrouded, Silver, Through Hole - Solder, Sealable, Signal, LEAVYSEAL



Application Specification

English