# ALR-M-PV ~ ACTIVE

## ALR

TE Internal #: 304514-000 ANSI Street Lighting Photocells, Worldwide, Thermal, 105 – 305 VAC, Industrial / Commercial, 1800 VA Load Rating (Ballast), Locking

## View on TE.com >

Connectors > Lighting Connectors > Street Lighting Controls > ANSI Street Lighting Photocells



Product Availability: Worldwide

Street Lighting Photo Control Technology: Thermal

Operating Voltage Range: 105 – 305 VAC

Grade: Commercial, Industrial

Load Rating (Ballast): 1800 VA

## Features

**TE** 

## Product Type Features

Light Sensor	CdS Photocell
Street Lighting Photo Control Technology	Thermal
Electrical Characteristics	
Operating Voltage Range	105 – 305 VAC
Load Rating (Ballast)	1800 VA
Load Rating (Tungsten)	1000 W
Fail Mode	On
Surge Protection	180 Joule
Operating Frequency	50 – 60 Hz
Body Features	
Compatible With Lamp Type	LED
Primary Product Color	Blue
Mechanical Attachment	
Mounting Options	Locking

**C** For support call+1 800 522 6752

## ALR-M-PV

ANSI Street Lighting Photocells, Worldwide, Thermal, 105 – 305 VAC, Industrial / Commercial, 1800 VA Load Rating (Ballast), Locking



Housing Features	
Housing Material	High Impact Noryl with UV-Stabilized Acrylic Window
Dimensions	
Product Diameter	74 mm[2.93 in]
Product Height	50 mm[1.96 in]
Usage Conditions	
Operating Temperature Range	-40 - 65 °C[-40 - 149 °F]
Operation/Application	
Turn OFF Time Delay	30 – 45 seconds
Turn ON Light Level	1.5 fc
Turn ON Time Delay	30 – 45 seconds
Industry Standards	
Agency/Standard	CSA, UL
Approved Standards	ANSI C136.10
Product Availability	
Product Availability	Worldwide

## Packaging Features

Packaging Quantity	6
Packaging Method	Box
Other	
Warranty	3 Years
Lighting Connector Comment	Dusk-to-dawn lighting control compatible with all solid state ballasts., Parking Lot, Security, & Street Lighting.
Grade	Commercial, Industrial
OFF/ON Ratio	5:1
Product Compliance	

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EUNot CompliantEU ELV Directive 2000/53/ECNot Compliant

### ALR-M-PV

ANSI Street Lighting Photocells, Worldwide, Thermal, 105 – 305 VAC, Industrial / Commercial, 1800 VA Load Rating (Ballast), Locking



China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) SVHC > Threshold: Cd (7.5% in Component Part) Aticle Safe Usage Statements: Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## **Compatible Parts**



## **Customers Also Bought**



## ALR-M-PV

ANSI Street Lighting Photocells, Worldwide, Thermal, 105 – 305 VAC, Industrial / Commercial, 1800 VA Load Rating (Ballast), Locking





## Documents

## **CAD** Files

## 3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_304514-000\_O.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_304514-000\_O.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_304514-000\_O.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages M SERIES PHOTOCONTROL

English