

#### **SOLISTRAND**

TE Internal #: 323698

Splices, Butt Splice, 12 – 10 AWG Wire Size, 3 – 6 mm² Wire Size, Serrated, .129 in [3.28 mm] Barrel Inside Diameter, 5180 – 13100


CMA Wire Size

View on TE.com >



Terminals & Splices > Splices











Wire Size: 3-6 mm<sup>2</sup>

Sealable: No

Splice Features: Serrated

Barrel Inside Diameter: 3.28 mm [ .129 in ]

### **Features**

## Product Type Features

Splice Accessory Type	Splice
Style Code	С
Sealable	No
Splice Type	Butt Splice
Compatible With Discrete Wire Type	Solid, Stranded
Wire Insulation Support Retention Type	Non-Insulation Support
Configuration Features	
Compatible With Wire & Cable Type	Discrete Wire

## Compatible With Wire & Cable Type

**Body Features** 

Product Weight	1.794 g
Splice Features	Serrated
Primary Product Color	Orange

### **Contact Features**

Contact Base Material	Nickel
-----------------------	--------



Barrel Type	Closed
Mechanical Attachment	
Wire Insulation Support	Without
Dimensions	
Outside Diameter	5.74 mm[.226 in]
Wire Size	5180 – 13100 CMA
Barrel Inside Diameter	3.28 mm[.129 in]
Terminal Material Thickness	1.07 mm[.042 in]
Product Length	17.86 mm[.703 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	649 °C[1200 °F]
Operation/Application	
Compatible With Wire Base Material	Copper
Industry Standards	
Government Qualified Splice	No
Packaging Features	
Packaging Quantity	500

## **Product Compliance**

Packaging Method

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Loose Piece



#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


# **Compatible Parts**



# Customers Also Bought















TE Part #ZPF00000000001734 13084-37 S 5020





### **Documents**

### **Product Drawings**

SPLICE, SOLIS BUTT HT 12-10

English

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_323698\_P.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_323698\_P.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_323698\_P.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_323698\_L.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_323698\_L.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_323698\_L.2d\_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### Datasheets & Catalog Pages

STRATO-THERM Terminals & Splices for High Temperature Applications

English

### **Product Specifications**

**Application Specification** 

English

Splices, Butt Splice, 12-10 AWG Wire Size, 3-6 mm<sup>2</sup> Wire Size, Serrated, .129 in [3.28 mm] Barrel Inside Diameter, 5180-13100 CMA Wire Size



Product Environmental Compliance

**Product Compliance** 

English

**Product Compliance** 

English