323796 ✔ ACTIVE

SOLISTRAND

TE Internal #: 323796

Splices, Butt Splice, 22 – 16 AWG Wire Size, .3 – 1.42 mm² Wire Size, Serrated, .061 in [1.55 mm] Barrel Inside Diameter, 509 – 3260 CMA Wire Size

View on TE.com >

Terminals & Splices > Splices

Wire Size: **.3 – 1.42 mm²**

Sealable: **No**

Splice Features: **Serrated**

Barrel Inside Diameter: **1.55 mm [.061 in]**

Features

Product Type Features

Splice Accessory Type	Splice
Sealable	No
Splice Type	Butt Splice
Compatible With Discrete Wire Type	Solid, Stranded
Wire Insulation Support Retention Type	Non-Insulation Support

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire

Body Features

Product Weight	.569 g
Splice Features	Serrated

Contact Features

	300 µin
Terminal Plating Material	Nickel
Contact Base Material	Copper

Barrel Type	Closed

Mechanical Attachment

Wire Insulation Support	Without

Dimensions

Outside Diameter	3.58 mm[.141 in]
Wire Size	509 – 3260 CMA
Barrel Inside Diameter	1.55 mm[.061 in]
Terminal Material Thickness	.79 mm[.031 in]
Product Length	14.68 mm[.578 in]

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	343 °C[650 °F]

Operation/Application

Compatible With Wire Base Material	Copper

Industry Standards

Government Qualified Splice	No

Packaging Features

Packaging Quantity	1000
Packaging Method	Loose Piece

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

TE Part # 46447
DAHT STRATO 22-10 ASSY

Customers Also Bought

TE Part #89-03KA-0U
9MM MV OUTPUT PRESSURE SENSOR



TE Part #NB-PTCO-160
Pt100, 2.0x2.3, Class B, PTFC101B1A0

TE Part #6609065-3
6EDP=F7689 S0

TE Part #1624202-2
23SE 10KA 6.35X50FL B7 CAT

TE Part #1-1478008-0
SMB R/A Plg PS 50Ohn Gold Pltd RG174A/U,

TE Part #1SNA113689R2400
ECP26

TE Part #1SNA163403R2000
CPP263

TE Part #GA30K5A416I
DISC- 30K 25'C +- 0.1'C

Documents

Product Drawings

SOLIS BUTT HR 22-16COM22-18MIL

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_323796_F.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_323796_F.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_323796_F.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

STRATO-THERM Terminals & Splices for High Temperature Applications

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English