

AMPOWER

TE Internal #: 324469 Splices, Butt Splice, 1.252 in [31.8 mm] Barrel Inside Diameter, 800 kcmil Wire Size, 750000 – 850000 CMA Wire Size, Copper, Gray, AMPOWER

View on TE.com >

Terminals & Splices > Splices > AMPOWER Butt Splice



Sealable: No

Barrel Inside Diameter: 31.8 mm [1.252 in]

Wire Size: 750000 – 850000 CMA

Contact Base Material: Copper

All AMPOWER Butt Splice (20)

Features

Product Type Features

Splice Accessory Type

Sealable



Splice

No

Splice Type	Butt Splice
Compatible With Discrete Wire Type	Stranded
Configuration Features	
Splice Configuration	Single to Single
Compatible With Wire & Cable Type	Discrete Wire
Body Features	
Primary Product Color	Gray
Contact Features	
	150 uin
	150 µin
Terminal Plating Material	Tin
Terminal Plating Material Contact Base Material	
	Tin
Contact Base Material	Tin Copper
Contact Base Material Barrel Type	Tin Copper

Splices, Butt Splice, 1.252 in [31.8 mm] Barrel Inside Diameter, 800 kcmil Wire Size, 750000 – 850000 CMA Wire Size, Copper, Gray, AMPOWER



Mechanical Attachment

Wire Insulation Support	Without	
Dimensions		
	1.518 in	
Barrel Inside Diameter	31.8 mm[1.252 in]	
Wire Size	750000 – 850000 CMA	
Product Length	75.18 mm[2.96 in]	
Usage Conditions		
Insulation Option	Uninsulated	
Operation/Application		
Compatible With Wire Base Material	Copper	
Industry Standards		
Agency/Standard	UL	
Approved Standards	UL E13288	
Packaging Eastures		
Packaging Features		
Packaging Quantity	25	

Other

Terminals & Splices Comment

Splice length is 75.18[2.96]., Tin Plate per ASTM B-545, Two Crimps necessary on each end.

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant	
EU ELV Directive 2000/53/EC	Compliant	
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold	
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC	
Halogen Content	Not Yet Reviewed for halogen content	
Solder Process Capability	Not applicable for solder process capability	

Splices, Butt Splice, 1.252 in [31.8 mm] Barrel Inside Diameter, 800 kcmil Wire Size, 750000 – 850000 CMA Wire Size, Copper, Gray, AMPOWER



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | AMPOWER



Busbar Connectors(13)	Knife Disconnects(13)	PCB Headers & Receptacles(2)	Power Cable Assemblies(7)
	and the second second		1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
Power Contacts(1)	Quick Disconnects(1)	Rectangular Power Connectors(6)	Spade Terminals(137)

Splices, Butt Splice, 1.252 in [31.8 mm] Barrel Inside Diameter, 800 kcmil Wire Size, 750000 – 850000 CMA Wire Size, Copper, Gray, AMPOWER





Customers Also Bought





Documents

Product Drawings SPLICE, AMPOWER BUTT 800MCM

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_324469_AA.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_324469_AA.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_324469_AA.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

S For support call+1 800 522 6752

Splices, Butt Splice, 1.252 in [31.8 mm] Barrel Inside Diameter, 800 kcmil Wire Size, 750000 – 850000 CMA Wire Size, Copper, Gray, AMPOWER



Datasheets & Catalog Pages AMPOWER Terminals and Splices Flyer

English

Agency Approvals

UL Report

English