




SOLISTRAND

TE Internal #: 328588

Splices, Butt Splice, 24 – 20 AWG Wire Size, .2 – .6 mm² Wire Size, Serrated, .043 in [1.09 mm] Barrel Inside Diameter, 320 – 1290 CMA Wire Size

[View on TE.com >](#)

Terminals & Splices > Splices



Wire Size: .2 – .6 mm²

Sealable: **No**

Splice Features: **Serrated**

Barrel Inside Diameter: 1.09 mm [.043 in]

Features

Product Type Features

Splice Accessory Type	Splice
Sealable	No
Splice Type	Butt Splice
Compatible With Discrete Wire Type	Solid
Wire Insulation Support Retention Type	Non-Insulation Support

Configuration Features

Number of Serrations	8
Compatible With Wire & Cable Type	Discrete Wire

Body Features

Splice Features	Serrated
-----------------	----------

Contact Features

Terminal Plating Thickness	1.27 μm[50 μin]
Terminal Plating Material	Gold
Contact Base Material	Copper



Barrel Type	Closed
-------------	--------

Mechanical Attachment

Wire Insulation Support	Without
-------------------------	---------

Dimensions

Recovered Inside Diameter	1.09 mm[.043 in]
---------------------------	------------------

Outside Diameter	2.67 mm[.105 in]
------------------	------------------

Wire Size	320 – 1290 CMA
-----------	----------------

Barrel Inside Diameter	1.09 mm[.043 in]
------------------------	------------------

Terminal Material Thickness	.51 mm[.02 in]
-----------------------------	----------------

Product Length	12.44 mm[.49 in]
----------------	------------------

Usage Conditions

Insulation Option	Uninsulated
-------------------	-------------

Operating Temperature Range	170 °C[338 °F]
-----------------------------	----------------

Operation/Application

Compatible With Wire Base Material	Copper
------------------------------------	--------

Industry Standards

Government Qualified Splice	No
-----------------------------	----

Packaging Features

Packaging Quantity	1000
--------------------	------

Packaging Method	Loose Piece
------------------	-------------

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
------------------------------	-----------

EU ELV Directive 2000/53/EC	Compliant
-----------------------------	-----------

China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
---	---

EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
--	---

Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
-----------------	---

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



REPRESENTATION ONLY

TE Part # 69363
DAHT STRATO SOLIS 26-20 ASSY

Customers Also Bought



TE Part #4108170001
HT-SCE-1/8-2.0-9



TE Part #2335890-1
AMPLIMITE SZ 1 RECEP 9 POS, ST STL SHEL




TE Part #7-2176371-6
RQ 0603 28K 0.1% 10PPM 5K RL



TE Part #CV3301-000
RW175 Heat shrink Tubing



TE Part #CV25362001
RW-175-E-1/16-X-STK




TE Part #323153-1
DG 22-16COM 22-18MIL HR AU R10



TE Part #3160793001
55A1121-26-6/9-9



TE Part #ZPF000000000036871
983-6SE 08-98 P6 L



Documents

Product Drawings

[SPLICE,SOLIS BUTT STRAP 24-20](#)

English

CAD Files

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_328588_K.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_328588_K.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_328588_K.3d_stp.zip](#)

English

Customer View Model

[ENG_CVM_328588_B.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_328588_B.3d_stp.zip](#)

English

Customer View Model

[ENG_CVM_328588_B.2d_dxf.zip](#)

English

3D PDF

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Environmental Compliance

[Product Compliance](#)

English

[Product Compliance](#)

English

328588

Splices, Butt Splice, 24 – 20 AWG Wire Size, .2 – .6 mm² Wire Size, Serrated, .043 in [1.09 mm] Barrel Inside Diameter, 320 – 1290 CMA Wire Size



[Agency Approvals](#)

[UL Report](#)

English