# 329636 ✓ ACTIVE

PIDG

TE Internal #: 329636

Closed Ring Tongue Terminal, 24 – 20 AWG, #2 / M2 Stud Size, 2.36 mm [.093 in] Stud Diameter, Closed Barrel, Straight, Tin, Partially Insulated, PIDG

View on TE.com >

Ring Terminal Product Type: **Closed Ring Tongue Terminal**

Wire Size: **320 – 1290 CMA**

Stud Size: **#2, M2**

All PIDG Ring Tongue Terminals (414)

Features

Product Type Features

Terminal Features	Sheared
Ring Terminal Product Type	Closed Ring Tongue Terminal
Stud Size	#2, M2
Sealable	No
Wire Insulation Support Retention Type	Insulation Support

Configuration Features

Number of Holes	1

Electrical Characteristics

Voltage Rating	300 V

Body Features

Product Weight	.362 g

Contact Features

Barrel Type	Closed

329636

Closed Ring Tongue Terminal, 24 – 20 AWG, #2 / M2 Stud Size, 2.36 mm [.093 in]
Stud Diameter, Closed Barrel, Straight, Tin, Partially Insulated, PIDG

Terminal Orientation	Straight
Terminal Plating Material	Tin

Mechanical Attachment

Wire Insulation Support	With

Dimensions

Wire Size	320 – 1290 CMA
Stud Diameter	2.36 mm[.093 in]
Tongue Thickness	.79 mm[.031 in]
Product Length	14.96 mm[.589 in]
Compatible Insulation Diameter (Max)	2.54 mm[.1 in]
Compatible Insulation Diameter Range	1.02 – 2.54 mm[.04 – .1 in]

Usage Conditions

Insulation Option	Partially Insulated
Operating Temperature Range	288 °C[550 °F]

Operation/Application

Compatible With Wire Base Material	Copper
Compatible With Wire Plating Material	Tin

Industry Standards

Government Qualified Terminal	No

Packaging Features

Packaging Quantity	1000
Packaging Method	Loose Piece

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC

Closed Ring Tongue Terminal, 24 – 20 AWG, #2 / M2 Stud Size, 2.36 mm [.093 in] Stud Diameter, Closed Barrel, Straight, Tin, Partially Insulated, PIDG

Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

TE Part # 59275
T-HEAD PIDG PG SH 26-20 ASSY

TE Part # 47907-1
DAHT PIDG 24-20 ASSY

TE Part # 59300
T-HEAD PIDG PG 26-16 ASSY

Also in the Series | PIDG

Compression Connectors(17)

Crimp Terminal Housings(1)

Crimp Wire Pins, Tabs & Ferrules(41)

Hand Crimping Tools(2)

Knife Disconnects(11)

PCB Terminals(7)

Quick Disconnects(49)

Ring Terminals(607)

329636

Closed Ring Tongue Terminal, 24 – 20 AWG, #2 / M2 Stud Size, 2.36 mm [.093 in]
Stud Diameter, Closed Barrel, Straight, Tin, Partially Insulated, PIDG

Spade Terminals(231)

Special Purpose Terminals(1)

Splices(45)

Customers Also Bought

TE Part #4-2176058-9
RLP73K 3A 1R0 5% 2K RL

TE Part #8-1393253-2
W69-X2Q110-30=M6/M7/M9/W6/W7

TE Part #1532212-1
M83513/01-DN, MCKS-N1-B-25PS

TE Part #5053012028
RNF-100-1/8-4-STK

TE Part #YDTS26F15-19SNV001
PLUG ASSY

TE Part #2-323913-1
N PIDG RING 26-22 2

TE Part #193495-000
D-150-0179

TE Part #1996390-1
SMPM STR CBL JACK

TE Part #YDL61H-20-28PNV001
HERM RECP

Documents

Product Drawings
TERMINAL,PIDG R 24-20 2

English

CAD Files
3D PDF

3D

Customer View Model
ENG_CVM_CVM_329636_F.2d_dxf.zip

329636

Closed Ring Tongue Terminal, 24 – 20 AWG, #2 / M2 Stud Size, 2.36 mm [.093 in]
Stud Diameter, Closed Barrel, Straight, Tin, Partially Insulated, PIDG

English

Customer View Model

ENG_CVM_CVM_329636_F.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_329636_F.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

PIDG TERMINALS & SPLICES Quick Reference Guide

English

Product Specifications

Application Specification

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English