

SOLISTRAND

TE Internal #: 33459-4


Closed Ring Tongue Terminal, 12 – 10 AWG, M8 / 5/16 Stud Size, 8.33 mm [.328 in] Stud Diameter, Closed Barrel, Straight, Unplated,

Uninsulated

View on TE.com >



Terminals & Splices > Ring Terminals



Ring Terminal Product Type: Closed Ring Tongue Terminal

Wire Size: 5180 – 13100 CMA

Stud Size: **5/16, M8**

Features

Product Type Features

Ring Terminal Product Type	Closed Ring Tongue Terminal
Stud Size	5/16, M8
Sealable	No
Wire Insulation Support Retention Type	Non-Insulation Support
Configuration Features	
Number of Holes	1
Contact Features	
Barrel Type	Closed
Terminal Orientation	Straight
Terminal Plating Material	Unplated
Mechanical Attachment	
Wire Insulation Support	Without
Dimensions	
Wire Size	5180 – 13100 CMA
Stud Diameter	8.33 mm[.328 in]



Tongue Thickness	.79 mm[.031 in]
Product Length	25.5 mm[1.004 in]
Barrel Inside Diameter	3.28 mm[.129 in]
Usage Conditions	

Compatible With Wire Base Material

Insulation Option	Uninsulated
Operating Temperature Range	170 °C[338 °F]
Operation/Application	

Copper

Tin

Compatible With Wire Plating Material

Industry Standards

Government Qualified Terminal	No	

Packaging Features

Packaging Quantity	500
Packaging Method	Loose Piece

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits



as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts















Customers Also Bought



















TE Part #2360001-3 MATE-AX/FAKRA II,CABLE ASSY

Documents

Product Drawings

TERMINAL, SOLIS R 12-10 5/16

English

CAD Files

3D PDF

English

Customer View Model

ENG_CVM_33459-4_M.2d_dxf.zip

English

Customer View Model

ENG_CVM_33459-4_M.3d_igs.zip

English

Customer View Model

ENG_CVM_33459-4_M.3d_stp.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_33459-4_BA.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_33459-4_BA.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_33459-4_BA.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

SOLISTRAND - QRG

English

RADIATION_RESISTANT_PRE-INSULATED_TERMINALS_SPLICES

English

Closed Ring Tongue Terminal, 12 – 10 AWG, M8 / 5/16 Stud Size, 8.33 mm [.328 in] Stud Diameter, Closed Barrel, Straight, Unplated, Uninsulated

