


AMP | Econoseal TE Internal #: 344273-1 Housing for Female Terminals, Wire-to-Wire, 3 Position, .188 in [4.8 mm] Centerline, Sealable, Black, Wire & Cable, Signal, Econoseal View on TE.com >



Connectors > Automotive Connectors > Automotive Housings



Connector System: Wire-to-Wire

Number of Positions: 3

Connector & Housing Type: Housing for Female Terminals

Centerline (Pitch): 4.8 mm [.188 in]

Sealable: Yes

Features

Product Type Features

Mixed & Hybrid Connector	No	
Connector Shape	Rectangular	
Connector System	Wire-to-Wire	
Connector & Housing Type	Housing for Female Terminals	

Sealable	Yes				
Connector & Contact Terminates To	Wire & Cable				
Primary Locking Feature	On the Terminal				
Configuration Features					
Blank Cavity Position	0				
Number of Positions	3				
Number of Rows	1				
Electrical Characteristics					
Nominal Voltage Architecture	12 V				
Body Features					
Cable Exit Angle	180°				
Primary Product Color	Black				
Connector & Keying Code	Neutral				
Contact Features					

Housing for Female Terminals, Wire-to-Wire, 3 Position, .188 in [4.8 mm] Centerline, Sealable, Black, Wire & Cable, Signal, Econoseal



Contact Size	1.8mm
Contact Type	Receptacle
Mating Tab Width	1.8 mm[.07 in]
Contact Current Rating (Max)	10 A
Mechanical Attachment	
Terminal Position Assurance	Yes
Strain Relief	Add By Accessory
Mating Alignment Type	Polarization Slot
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	PA
Centerline (Pitch)	4.8 mm[.188 in]
Dimensions	
Connector Height	19.7 mm[.78 in]
Product Width	25.4 mm[1 in]
Product Length	27.6 mm[1.09 in]
Compatible Insulation Diameter Range	1.6 – 2.8 mm[.06 – .1 in]
Wire Size	.2 – 2 mm ²
Usage Conditions	
Operating Temperature (Max)	105 °C[221 °F]
Operating Temperature Range	-30 – 105 °C[-22 – 221 °F]
Operation/Application	
Circuit Application	Signal
Industry Standards	
Degree of Protection	IPX4
UL Flammability Rating	Not tested
Packaging Features	
Packaging Quantity	500
Packaging Method	Bag
Other	
Serviceable	Yes

Housing for Female Terminals, Wire-to-Wire, 3 Position, .188 in [4.8 mm] Centerline, Sealable, Black, Wire & Cable, Signal, Econoseal



Connector Position Assurance Capable

No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Housing for Female Terminals, Wire-to-Wire, 3 Position, .188 in [4.8 mm] Centerline, Sealable, Black, Wire & Cable, Signal, Econoseal




TE Part # 347703-1 3 WAY PERIPHERAL SEAL SILIC

Also in the Series | Econoseal



Connector Seals & Cavity Plugs(19)	Insertion & Extraction Tools(7)	Other Automotive Connector	PCB Headers & Receptacles(4)
		Accessories(5)	



Customers Also Bought



Housing for Female Terminals, Wire-to-Wire, 3 Position, .188 in [4.8 mm] Centerline, Sealable, Black, Wire & Cable, Signal, Econoseal





Documents

TE Part #345808-1

.070"RECEPTACLE ECON.3

Product Drawings 3 WAY REC. HSG. SIL. SEALECONO

TE Part #345256-1

HSGECONO

ANTI-BACKOUT 3WAY REC

English

CAD Files

3D PDF

3D

Customer View Model ENG_CVM_CVM_344273-1_G.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_344273-1_G.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_344273-1_G.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.