4-1105300-1 ACTIVE

SOLARLOK

TE Internal #: 4-1105300-1

Connector Contacts, Pin, Silver, 400 VDC, 14 AWG Wire Size, 2.5 mm 2 Wire Size, Crimp, Copper Alloy, Wire & Cable, -40 – 275 °F

[-40 – 125 °C]

View on TE.com >



Connectors > Rectangular Connectors > Connector Contacts



Contact Type: Pin

Contact Mating Area Plating Material: Silver

Operating Voltage: 400 VDC

Wire Size: 2.5 mm²

Features

Product Type Features

Connector & Contact Terminates To	Wire & Cable
Electrical Characteristics	
Contact Resistance	$3~\text{m}\Omega$
Operating Voltage	400 VDC
Contact Features	
Contact Type	Pin
Contact Mating Area Plating Material	Silver
Contact Base Material	Copper Alloy
Contact Current Rating (Max)	16 A
Termination Features	
Termination Features Termination Method to Wire & Cable	Crimp
	Crimp
Termination Method to Wire & Cable	Crimp 2.5 mm ²
Termination Method to Wire & Cable Dimensions	
Termination Method to Wire & Cable Dimensions Wire Size	
Termination Method to Wire & Cable Dimensions Wire Size Usage Conditions	2.5 mm ²
Termination Method to Wire & Cable Dimensions Wire Size Usage Conditions Operating Temperature Range	2.5 mm ²



Packaging Quantity	50
Packaging Method	Bag
Other	
Connector Contacts Comment	Use with HTS Series HVT inserts

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) SVHC > Threshold: Pb (3.5% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts























Customers Also Bought







RNF-100-2-X-STK











Documents

Connector Contacts, Pin, Silver, 400 VDC, 14 AWG Wire Size, 2.5 mm² Wire Size, Crimp, Copper Alloy, Wire & Cable, -40 – 275 °F [-40 – 125 °C]



Product Drawings

HVT-C-Sti.Ag.2,5 qmm

English

Product Specifications

Application Specification

English

Product Environmental Compliance

TE Material Declaration

English