# KUP-11D15-48 ✓ ACTIVE

### Potter & Brumfield | Potter & Brumfield KUP

TE Internal #: 4-1393117-7

Power Relays, Industrial Panel Plug-In, Monostable, DC, 1300 mW Coil Power Rating DC, 1800  $\Omega$  Coil Resistance, Potter & Brumfield KUP

View on TE.com >



Relays, Contactors & Switches > Relays > Power Relays



Power Relay Type: Industrial Panel Plug-In
Coil Magnetic System: Monostable, DC

Coil Power Rating DC: 1300 mW

Coil Resistance:  $1800 \Omega$ 

Coil Special Features: UL Coil Insulation Class B

#### **Features**

#### **Product Type Features**

Power Relay Type	Industrial Panel Plug-In
Electrical Characteristics	
Insulation Initial Dielectric Between Coil & Contact Class	1500 – 2500 V
Insulation Initial Dielectric Between Contacts & Coil	2200 Vrms
Actuating System	DC
Insulation Initial Dielectric Between Open Contacts	1200 Vrms
Contact Limiting Making Current	10 A
Contact Limiting Short-Time Current	10 A
Contact Limiting Continuous Current	10 A
Coil Power Rating Class	1000 – 1500 mW
Insulation Initial Dielectric Between Adjacent Contacts	2200 Vrms
Insulation Initial Resistance	100 ΜΩ
Contact Limiting Breaking Current	10 A
Coil Magnetic System	Monostable, DC
Coil Power Rating DC	1300 mW
Coil Resistance	1800 Ω
Coil Special Features	UL Coil Insulation Class B
Coil Voltage Rating	48 VDC



Contact Switching Load (Min)	300mA @ 12V
Contact Voltage Rating	240 VAC
Body Features	
Product Weight	85 g[2.988 oz]
Contact Features	
Contact Arrangement	2 Form C (CO)
Contact Current Class	5 – 10 A, 16 A
Contact Current Rating (Max)	10 A
Contact Material	AgCdO
Contact Number of Poles	2
Relay Terminal Type	Quick Connect, Solder
Mechanical Attachment	
Relay Mounting Type	Socket
Dimensions	
Dimensions  Length Class (Mechanical)	35 – 40 mm
	35 – 40 mm 40 – 50 mm
Length Class (Mechanical)	
Length Class (Mechanical) Height Class (Mechanical)	40 – 50 mm
Length Class (Mechanical)  Height Class (Mechanical)  Width Class (Mechanical)	40 – 50 mm 30 – 40 mm
Length Class (Mechanical)  Height Class (Mechanical)  Width Class (Mechanical)  Product Width	40 – 50 mm 30 – 40 mm 35.7 mm[1.405 in]
Length Class (Mechanical)  Height Class (Mechanical)  Width Class (Mechanical)  Product Width  Product Length	40 – 50 mm 30 – 40 mm 35.7 mm[1.405 in] 38.9 mm[1.55 in]
Length Class (Mechanical)  Height Class (Mechanical)  Width Class (Mechanical)  Product Width  Product Length  Product Height	40 – 50 mm 30 – 40 mm 35.7 mm[1.405 in] 38.9 mm[1.55 in]
Length Class (Mechanical)  Height Class (Mechanical)  Width Class (Mechanical)  Product Width  Product Length  Product Height  Usage Conditions	40 – 50 mm 30 – 40 mm 35.7 mm[1.405 in] 38.9 mm[1.55 in] 50 mm[1.97 in]
Length Class (Mechanical)  Height Class (Mechanical)  Width Class (Mechanical)  Product Width  Product Length  Product Height  Usage Conditions  Environmental Ambient Temperature Class	40 – 50 mm 30 – 40 mm 35.7 mm[1.405 in] 38.9 mm[1.55 in] 50 mm[1.97 in]
Length Class (Mechanical)  Height Class (Mechanical)  Width Class (Mechanical)  Product Width  Product Length  Product Height  Usage Conditions  Environmental Ambient Temperature Class  Environmental Ambient Temperature (Max)	40 – 50 mm 30 – 40 mm 35.7 mm[1.405 in] 38.9 mm[1.55 in] 50 mm[1.97 in] 50 – 70 °C 70 °C[158 °F]
Length Class (Mechanical)  Height Class (Mechanical)  Width Class (Mechanical)  Product Width  Product Length  Product Height  Usage Conditions  Environmental Ambient Temperature Class  Environmental Ambient Temperature (Max)  Operating Temperature Range	40 – 50 mm 30 – 40 mm 35.7 mm[1.405 in] 38.9 mm[1.55 in] 50 mm[1.97 in] 50 – 70 °C 70 °C[158 °F]

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold



EU REACH Regulation (EC) No. 1907/2006

Current ECHA Candidate List: JUNE 2023

(235)

Candidate List Declared Against: JUNE

2022 (224)

SVHC > Threshold:

Cadmium oxide (10% in Component Part)

Article Safe Usage Statements:

Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Halogen Content

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC

Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts













Also in the Series | Potter & Brumfield KUP





Power Relays(155)



## Customers Also Bought



TE Part #1-1393114-1 KUEP-7D15-24=KU



TE Part #1393114-1 KUEP-3D15-24=KU-



TE Part #1393143-6 27E122=SOCKET,KRP,8,SCW,PLES





TE Part #4-1393117-5 KUP-11D15-24=KU



TE Part #8-1393113-8 KUEP-11D15-48=KU



TE Part #2-1393117-2 KUP-11A15-240=KU



KUEP-7D15-48=KU

TE Part #1443747-2 CABLE ASM MOD PLUG, SHIELDED TE Part #8-1393131-9 PRDA-11DJA-48=PRD

### **Documents**

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_4-1393117-7\_D.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_4-1393117-7\_D.3d\_igs.zip



English

**Customer View Model** 

ENG\_CVM\_CVM\_4-1393117-7\_D.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

KUP Series Panel Plug-in Relay

English

**Product Specifications** 

Definitions General Purpose Relays

English

**Agency Approvals** 

UL

English