

FullAXS

TE Internal #: 4-2061348-5 Rugged Fiber Cable Assemblies, Fiber Optic Cable (FOCAB), .216 in [5.5 mm] Diameter, 2 Fibers, Blue, Blue, Black Cable, Standard Boot Type (Left)

View on TE.com >

Fiber Optics > Fiber Optic Cable Assemblies > Rugged Fiber Cable Assemblies



Fiber Optic Cable Type: Fiber Optic Cable (FOCAB)

Cable Assembly Fiber Diameter: 9/125 µm

Outside Cable Diameter: 5.5 mm [.216 in]

Number of Fibers: 2

Connector Color (End A): Blue

Features

connectivity

Product Type Features

Protection & Strain Relief Accessory Type	Protective Cap	
Fiber Optic Cable Type	Fiber Optic Cable (FOCAB)	
Fiber Optic Mode	Singlemode	
Connector Type (End A)	LC with ODVA Adapter Plug	
Connector Type (End B)	LC Duplex Plug	
Cable Assembly Type	LC with ODVA Adapter to LC Duplex	
Fiber Type	SM	
Configuration Features		
Exit Angle to Exit Angle	180° to 180°	
Number of Fibers	2	
Cable Buffering	Tight Buffer	
Body Features		
Connector Color (End A)	Blue	
Connector Color (End B)	Blue	

4-2061348-5

Rugged Fiber Cable Assemblies, Fiber Optic Cable (FOCAB), .216 in [5.5 mm] Diameter, 2 Fibers, Blue, Blue, Black Cable, Standard Boot Type (Left)



Cable Color	Black	
Boot Type (Left)	Standard	
Boot Type (Right)	Bend Limiting	
Boot Color (Left)	Black	
Boot Color (Right)	Blue	
Dimensions		
Cable Assembly Fiber Diameter	9/125 µm	
Outside Cable Diameter	5.5 mm[.216 in]	
Other		
Cable Assembly Length	44.5 – 45.5 m	
Product Compliance For compliance documentation, visit the product page on TE.com>		
EU RoHS Directive 2011/65/EU	Compliant with Exemptions	
EU ELV Directive 2000/53/EC	Compliant with Exemptions	
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold	
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235)	

Halogen Content

Solder Process Capability

Candidate List Declared Against: JUL 2017 (174) SVHC > Threshold: Not Yet Reviewed

Not Yet Reviewed for halogen content

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

4-2061348-5

Rugged Fiber Cable Assemblies, Fiber Optic Cable (FOCAB), .216 in [5.5 mm] Diameter, 2 Fibers, Blue, Blue, Black Cable, Standard Boot Type (Left)



Compatible Parts



Customers Also Bought



TE Part #2273110-5	TE Part #7-173977-0	TE Part #3-1589477-5	TE Part #5-1589477-9
M8 strgt socket to M12 strgt plug AA	CT MT REC 10P BLACK	STM037SC2DC020Q = WDUALOBE	STM051SC2DC060Q = WDUALOBE





TE Part #2304890-1 CA,ET, 4POS, NO PULL-TAB,NO DETECT,SHIEL TE Part #YDTS20W25-20JNC001 RECP ASSY

Documents

Product Drawings FOSM LEAD LC/DPX ODVA - LC/DPX 45M English CAD Files 3D PDF

3D

4-2061348-5

Rugged Fiber Cable Assemblies, Fiber Optic Cable (FOCAB), .216 in [5.5 mm] Diameter, 2 Fibers, Blue, Blue, Black Cable, Standard Boot Type (Left)



Customer View Model

ENG_CVM_CVM_4-2061348-5_E.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_4-2061348-5_E.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_4-2061348-5_E.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages Fiber Optic Products_0412

English