

MTA 100

TE Internal #: 4-641190-6

Standard Rectangular Connectors, Connector Assembly,

Receptacle, Mating Retention, Insulation Displacement (IDC), Wire-

to-Board, MTA 100

View on TE.com >



Connectors > Rectangular Connectors > Standard Rectangular Connectors > Nylon Gold Plated Receptacle: 2.54 mm, no Mating Alignment



Connector Product Type: Connector Assembly

Connector & Housing Type: Receptacle

Mating Alignment: Without

Mating Retention: With

Mating Retention Type: Locking Ramp

All Nylon Gold Plated Receptacle: 2.54 mm, no Mating Alignment (89)

Features

Product Type Features

Compatible With Discrete Wire Type	Stranded
Connector Product Type	Connector Assembly
Connector & Housing Type	Receptacle
Connector System	Wire-to-Board
Insertion Force Type	Normal
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Configuration Features	

Configuration Features

Number of Cavities	16
Contacts Preloaded	Yes
Number of Positions	16
Number of Rows	1

Electrical Characteristics

Contact Features

Contact Type	Receptacle
Wire Contact Termination Area Plating Material	Tin



Contact Underplating Material Contact Mating Area Plating Material Contact Retention Within Housing With Contact Current Rating (Max) Termination Features Termination Method to Wire & Cable Insulation Displacement (IDC) Mechanical Attachment Contact Retention Type Within Housing Locking Lance Mating Alignment Without Mating Retention Mating Retention Type Connector Mounting Type Connector Mounting Type Housing Features
Contact Retention Within Housing Contact Current Rating (Max) Termination Features Termination Method to Wire & Cable Insulation Displacement (IDC) Mechanical Attachment Contact Retention Type Within Housing Locking Lance Mating Alignment Without Mating Retention Mating Retention Type Connector Mounting Type Cable Mount (Free-Hanging) Housing Features
Contact Current Rating (Max) Termination Features Termination Method to Wire & Cable Insulation Displacement (IDC) Mechanical Attachment Contact Retention Type Within Housing Mating Alignment Without Mating Retention Mating Retention Type Locking Ramp Connector Mounting Type Cable Mount (Free-Hanging) Housing Features
Termination Features Termination Method to Wire & Cable Insulation Displacement (IDC) Mechanical Attachment Contact Retention Type Within Housing Locking Lance Mating Alignment Without Mating Retention With Mating Retention Type Locking Ramp Connector Mounting Type Cable Mount (Free-Hanging) Housing Features
Termination Method to Wire & Cable Mechanical Attachment Contact Retention Type Within Housing Locking Lance Mating Alignment Without Mating Retention Mating Retention Type Locking Ramp Connector Mounting Type Cable Mount (Free-Hanging) Housing Features
Mechanical Attachment Contact Retention Type Within Housing Locking Lance Mating Alignment Without Mating Retention With Mating Retention Type Locking Ramp Connector Mounting Type Cable Mount (Free-Hanging) Housing Features
Contact Retention Type Within Housing Mating Alignment Without Mating Retention With Mating Retention Type Locking Ramp Connector Mounting Type Cable Mount (Free-Hanging) Housing Features
Mating Alignment Mating Retention With Mating Retention Type Locking Ramp Connector Mounting Type Cable Mount (Free-Hanging) Housing Features
Mating Retention Mating Retention Type Locking Ramp Connector Mounting Type Cable Mount (Free-Hanging) Housing Features
Mating Retention Type Connector Mounting Type Cable Mount (Free-Hanging) Housing Features
Connector Mounting Type Cable Mount (Free-Hanging) Housing Features
Housing Features
Housing Material Nylon 6/6
Housing Color Red
Centerline (Pitch) 2.54 mm[.1 in]
Dimensions
Connector Height 13.21 mm[.52 in]
Product Width 6.99 mm[.275 in]
Product Length 40.64 mm[1.6 in]
Wire Size .3 – .4 mm ²
Usage Conditions
Operating Temperature Range -55 – 105 °C[-67 – 221 °F]
Operation/Application
Shielded
Circuit Application Signal
Industry Standards
CSA Rating LR 7189
UL Rating Recognized
Agency/Standard CSA, UL
Approved Standards UL E28476
UL Flammability Rating UL 94V-2



Packaging Features

Packaging Quantity	250
Packaging Method	Bag/Box

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts














TE Part # 58579-1 MTA 100 MANUAL TOOL ASSEMBLY DISCRETE



TE Part # 58039-1 MTA 100 ARBOR FIXTURE DISCRETE RBN CABLE



Also in the Series | MTA 100



Connector Caps & Covers(69)



Insertion & Extraction Tools(2)



PCB Connector Keying(1)



PCB Headers & Receptacles(440)



Standard Rectangular Connectors(495)



Wire-to-Board Connector Assemblies & Housings(1)



Wire-to-Board Connector Contacts(8)

Customers Also Bought



TE Part #327583
SPLICE BUTT PIDG 16-14/22-18



TE Part #2-320554-1 PIDG R 22-16 COMM 22-18 MIL 8



TE Part #5745395-2 HD-20 RCPT 9P RA 318 FFSCRLK





TE Part #9-1437652-5 6PCV-06-006=6PCV ASSEMBLY



TE Part #2-1437653-5 6PCV-09-006=6PCV ASSEMBLY



TE Part #1393766-9 R10-E1X2-V700=R10







Documents

Product Drawings

16P MTA100 CONN ASSY RED LF

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_4-641190-6_S.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_4-641190-6_S.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_4-641190-6_S.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English

Agency Approvals

Agency Approval Document

English