4-881545-2 - ACTIVE

#### AMPMODU

TE Internal #: 4-881545-2 Board-to-Board Jumpers & Shunts, Novo, Open Top, 2 Position, .1 in [2.54 mm] Centerline, Signal, -85 – 140 °F [-65 – 60 °C] View on TE.com > **TE** connectivity

Connectors > PCB Connectors > Board-to-Board Connectors > Board-to-Board Jumpers & Shunts



Shunt Type: Novo Shunt Style: Open Top Connector System: Board-to-Board Number of Positions: 2 Centerline (Pitch): 2.54 mm [.1 in]

### Features

#### Product Type Features

Connector System

Connector & Contact Terminates To

#### **Configuration Features**

Number of Positions

2

Board-to-Board

Printed Circuit Board

#### **Electrical Characteristics**

Termination Resistance	15 mΩ
Body Features	
Handle	With
Primary Product Color	Black
Contact Features	
Contact Mating Area Plating Material	Tin
Contact Base Material	Phosphor Bronze
Shunt Type	Novo
Shunt Style	Open Top
Contact Current Rating (Max)	3 A
Mechanical Attachment	
Connector Mounting Type	Board Mount
Housing Features	

**C** For support call+1 800 522 6752

#### 4-881545-2

Board-to-Board Jumpers & Shunts, Novo, Open Top, 2 Position, .1 in [2.54 mm] Centerline, Signal, -85 – 140 °F [-65 – 60 °C]



Housing Material	Thermoplastic	
Centerline (Pitch)	2.54 mm[.1 in]	
Dimensions		
Product Height	10.9 mm[.429 in]	
Usage Conditions		
Operating Temperature Range	-65 – 60 °C[-85 – 140 °F]	
Operation/Application		
Circuit Application	Signal	
Industry Standards		
UL Flammability Rating	UL 94V-0	
Packaging Features		
Jumper & Shunt Packaging	Loose Piece	
Packaging Quantity	14000	
Packaging Method	Bag	

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits

#### 4-881545-2

Board-to-Board Jumpers & Shunts, Novo, Open Top, 2 Position, .1 in [2.54 mm] Centerline, Signal, -85 – 140 °F [-65 – 60 °C]



as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

## Compatible Parts



# Customers Also Bought



ETE		
TE Part #8-1437627-1 G12A=BUTTON GUARD ALUM	TE Part #1SNA176663R0000 BJMI6-2	TE Part #1-521204-6 HSG, POS LOCK, .250 SERIES, 2 POSITION

## Documents

Product Drawings AMP SHUNT ASS'Y

English

**CAD** Files

Customer View Model

ENG\_CVM\_4-881545-2\_K.3d\_stp.zip

English

Customer View Model

ENG\_CVM\_4-881545-2\_K.2d\_dxf.zip

English

#### 4-881545-2

Board-to-Board Jumpers & Shunts, Novo, Open Top, 2 Position, .1 in [2.54 mm] Centerline, Signal, -85 – 140 °F [-65 – 60 °C]



Customer View Model

ENG\_CVM\_4-881545-2\_K.3d\_igs.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

## Datasheets & Catalog Pages AMPMODU\_INTERCONNECTION\_SYSTEM\_SECTION\_6\_7AND8

English

Agency Approvals Agency Approval Document

English