TE Internal #: 414963-1

SMB RF Interface, Jack, 50  $\Omega$ , Snap-Fit, 4 GHz Operating

Frequency, Cable-to-Board, 1 Position, Printed Circuit Board, Panel


Mount

View on TE.com >



Connectors > RF Connectors > Coax Connectors > SMB Connector: Jack, Right-Angle Mount, Mated Outer Dia. 4.75mm











RF Interface: SMB

RF Connector Style: Jack

RF Connector Mated Outer Diameter (Approximate): 4.75 mm [ .187 in ]

Impedance:  $50 \Omega$ 

RF Connector Coupling Mechanism: Snap-Fit

All SMB Connector: Jack, Right-Angle Mount, Mated Outer Dia. 4.75mm (10)

# Features

# **Product Type Features**

Connector Shape	Rectangular
Connector Product Type	Connector Assembly
RF Interface	SMB
RF Connector Style	Jack
Connector System	Cable-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

## **Configuration Features**

PCB Mount Orientation	Right Angle
Number of Positions	1
Number of Coaxial Contacts	1

## **Electrical Characteristics**

Impedance	50 Ω	



## **Body Features**

Body Material	Zinc Alloy
Body Plating Material	Gold

#### **Contact Features**

RF Connector Center Contact Underplating Material	Nickel
RF Connector Center Contact Plating Material	Gold
RF Connector Center Contact Material	Brass

#### **Termination Features**

Termination Post & Tail Length	2.79 mm[.109 in]
Termination Method to Printed Circuit Board	Through Hole - Solder

### Mechanical Attachment

RF Connector Coupling Mechanism	Snap-Fit
Connector Mounting Type	Panel Mount
RF Contact Captivation Method	Mechanical
Detent	Without

## **Dimensions**

Profile Height from PCB	7.67 mm[.302 in]
RF Connector Mated Outer Diameter (Approximate)	4.75 mm[.187 in]

# **Usage Conditions**

Operating Temperature Range	-65 – 165 °C[-85 – 329 °F]
-----------------------------	----------------------------

## Operation/Application

Operating Frequency	4 GHz	

# **Packaging Features**

### Other

Additional Features	Board Standoff
Grade	Consumer
Dielectric Material	PTFE

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>



EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235)  Candidate List Declared Against: JUNE 2023 (235)  SVHC > Threshold:  Pb (3.7% in Component Part)  Article Safe Usage Statements:  Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts





# **Customers Also Bought**





TE Part #5787962-1
.8MM CHAMP STACK RCPT ASSY



TE Part #5-102699-9 20 MODII HDR DRST SHRD A/PIN



TE Part #5767096-8 MICT,REC,038,ASY,.025,TAPE,CAP



FREE,48,

=TE

TE Part #1825265-2 MSS4200RG04=4PDT SL SW R/A AU



TE Part #DTF13-4P HDR, 4P, BLK, RA, SN/NI/CU



TE Part #2284170-1 SFP+ ENHANCED 1X5 CAGE ASSEMBLY PRESS FI



TE Part #2198235-3 SFP+ Enhanced 1x6, Networking Heatsink



TE Part #1766685-1 CONN,SKT,LONG SLDR,MC-P3S0

TE Part #1820974-1 FASTON STRAP ALIZE

## **Documents**

Product Drawings
SMB PCB R/A JACK

English

#### **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_414963-1\_H1.2d\_dxf.zip

English

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_414963-1\_H1.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_414963-1\_H1.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

SMB RF Interface, Jack, 50  $\Omega$ , Snap-Fit, 4 GHz Operating Frequency, Cable-to-Board, 1 Position, Printed Circuit Board, Panel Mount



#### **SMB Connectors**

English

Product Environmental Compliance

MD\_414963-1\_01162012536

English

MD\_414963-1\_01162012536

English