TE Internal #: 42639-1

Closed Ring Tongue Terminal, 14 – 12 AWG, #10 Stud Size, 5 mm [.

19 in] Stud Diameter, Open Barrel, Straight, Tin, Uninsulated

View on TE.com >



Terminals & Splices > Ring Terminals











Ring Terminal Product Type: Closed Ring Tongue Terminal

Wire Size: 4106 – 6529 CMA

Stud Size: #10

Features

Product Type Features

Shape Description	D Shaped
Ring Terminal Product Type	Closed Ring Tongue Terminal
Stud Size	#10
Sealable	No
Compatible With Discrete Wire Type	Stranded
Wire Insulation Support Retention Type	Insulation Support
Configuration Features	
Number of Holes	1
Body Features	
Product Weight	2.058 g
Contact Features	
Contact Base Material	Brass
Barrel Type	Open
Terminal Orientation	Straight
Terminal Plating Material	Tin
Contact Underplating Material	None



Mechanical Attachment

Wire Insulation Support	With
Dimensions	
	.17 in
Wire Size	4106 – 6529 CMA
Stud Diameter	5 mm[.19 in]
Tongue Thickness	1.02 mm[.04 in]
Product Length	24.13 mm[.95 in]
Barrel Inside Diameter	2.54 mm, 4.82 mm[.1 in][.19 in]
Compatible Insulation Diameter (Max)	5.33 mm[.21 in]
Compatible Insulation Diameter Range	4.32 – 5.33 mm[.17 – .21 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	110 °C[230 °F]
Operation/Application	
Compatible With Wire Base Material	Copper
	Copper
Compatible With Wire Base Material	Copper
Compatible With Wire Base Material Industry Standards	
Compatible With Wire Base Material Industry Standards Government Qualified Terminal	

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC



Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts



TE Part # 42863-2 RING CRIMP 12-10 AWG TPBR



RING CRIMP 12-10 AWG TPBR



TE Part # 42864-1 RING CRIMP 12-10 AWG BR





















Customers Also Bought







TE Part #4-521097-2 ULTRA-FAST 250 ASY TAB 12-10 AWG TPBR



TE Part #2-520193-2 ULTRA-FAST 187 ASY REC 22-18 TPBR



TE Part #61944-2 250 FASTON REC 18-14 AWG TPBR



TE Part #3-520140-2 ULTRA-FAST 250 ASY REC 16-14 AWG TPBR



TE Part #42801-2 187 FASTON REC 20-16 AWG TPBR



TE Part #4-1393159-3 20C297=HOLD DOWN SPRING PER PR







Documents

Product Drawings

RING TERMINAL 14-12 AWG BR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_42639-1_R_c-42639-1-r.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_42639-1_R_c-42639-1-r.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_42639-1_R_c-42639-1-r.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Closed Ring Tongue Terminal, 14 – 12 AWG, #10 Stud Size, 5 mm [.19 in] Stud Diameter, Open Barrel, Straight, Tin, Uninsulated



Application Specification

English