TE Internal #: 42864-1

Closed Ring Tongue Terminal, 12 – 10 AWG, #10 Stud Size, 5 mm [. 197 in] Stud Diameter, Open Barrel, Straight, Unplated, Uninsulated

View on TE.com >



Terminals & Splices > Ring Terminals











Ring Terminal Product Type: Closed Ring Tongue Terminal

Wire Size: **6529 – 10382 CMA**

Stud Size: #10

Features

Product Type Features

Shape Description	Circular/Oval
Ring Terminal Product Type	Closed Ring Tongue Terminal
Stud Size	#10
Sealable	No
Compatible With Discrete Wire Type	Stranded
Wire Insulation Support Retention Type	Insulation Support
Configuration Features	
Number of Holes	1
Body Features	
Product Weight	1.858 g
Contact Features	
Contact Base Material	Brass
Barrel Type	Open
Terminal Orientation	Straight
Terminal Plating Material	Unplated



Mechanical Attachment

Wire Insulation Support	With
Dimensions	
	.17 in
Wire Size	6529 – 10382 CMA
Stud Diameter	5 mm[.197 in]
Tongue Thickness	1.02 mm[.04 in]
Product Length	23.37 mm[.92 in]
Barrel Inside Diameter	2.54 mm, 4.82 mm[.1 in][.19 in]
Compatible Insulation Diameter (Max)	5.33 mm[.21 in]
Compatible Insulation Diameter Range	4.32 – 5.33 mm[.17 – .21 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	110 °C[230 °F]
Operation/Application	
Campatible With Mire Dage Material	
Compatible With Wire Base Material	Copper
Industry Standards	Copper
	Copper
Industry Standards	
Industry Standards Government Qualified Terminal	

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC



Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 42191-1
FLAG TERMINAL TERMINAL 18-12
AWG TPBR



TE Part # 42639-1 RING TERMINAL 14-12 AWG BR



TE Part # 2150286-2 OCEAN_2.0_Applicator-E-180F300F



TE Part # 60399-1 RING TERMINAL 12-10 AWG TPCU



TE Part # 7-2150286-2
OCEAN_2.0_Applicator-E-180F300F



Customers Also Bought























Documents

Product Drawings

RING CRIMP 12-10 AWG BR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_42864-1_N_c-42864-1-n.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_42864-1_N_c-42864-1-n.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_42864-1_N_c-42864-1-n.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English