
# 440146-5 - ACTIVE

### MIS

TE Internal #: 440146-5 Housing, Receptacle, Wire-to-Board, 5 Position, .049 in [1.25 mm] Centerline, Crimp, 1 Row, Natural, Mating Retention, Wire & Cable, MIS

### View on TE.com >

Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Connector Assemblies & Housings



Connector Product Type: Housing Connector & Housing Type: Receptacle Connector System: Wire-to-Board Number of Positions: 5 Centerline (Pitch): 1.25 mm [.049 in ]

### Features



### Product Type Features

| Connector Product Type                | Housing       |  |  |  |  |  |  |  |  |
|---------------------------------------|---------------|--|--|--|--|--|--|--|--|
| Connector & Housing Type              | Receptacle    |  |  |  |  |  |  |  |  |
| Connector System                      | Wire-to-Board |  |  |  |  |  |  |  |  |
| Sealable                              | No            |  |  |  |  |  |  |  |  |
| Connector & Contact Terminates To     | Wire & Cable  |  |  |  |  |  |  |  |  |
| Configuration Features                |               |  |  |  |  |  |  |  |  |
| Number of Positions                   | 5             |  |  |  |  |  |  |  |  |
| Number of Rows                        | 1             |  |  |  |  |  |  |  |  |
| Electrical Characteristics            |               |  |  |  |  |  |  |  |  |
| Dielectric Withstanding Voltage (Max) | 250 VAC       |  |  |  |  |  |  |  |  |
| Insulation Resistance                 | 100 ΜΩ        |  |  |  |  |  |  |  |  |
| Operating Voltage                     | 100 VAC       |  |  |  |  |  |  |  |  |
| Body Features                         |               |  |  |  |  |  |  |  |  |
| Primary Product Color                 | Natural       |  |  |  |  |  |  |  |  |

**C** For support call+1 800 522 6752

Housing, Receptacle, Wire-to-Board, 5 Position, .049 in [1.25 mm] Centerline, Crimp, 1 Row, Natural, Mating Retention, Wire & Cable, MIS



### **Contact Features**

| Contact Layout                         | Inline                        |
|--|-------------------------------|
| Contact Type                           | Socket                        |
| Contact Base Material                  | Copper Alloy                  |
| Contact Current Rating (Max)           | 1 A                           |
| Termination Features                   |                               |
| Termination Method to Wire & Cable     | Crimp                         |
| Mechanical Attachment                  |                               |
| Strain Relief                          | Without                       |
| Panel Mount Feature                    | Without                       |
| PCB Mount Retention                    | Without                       |
| Mating Retention Type                  | Detent                        |
| Mating Retention                       | With                          |
| Connector Mounting Type                | Cable Mount (Free-Hanging)    |
| Housing Features                       |                               |
| Housing Entry Configuration            | Both Ends Closed              |
| Housing Material                       | Thermoplastic                 |
| Centerline (Pitch)                     | 1.25 mm[.049 in]              |
| Dimensions                             |                               |
| Connector Length                       | 8 mm[.315 in]                 |
| Connector Height                       | 3.15 mm[.124 in]              |
| Connector Width                        | 3.95 mm[.156 in]              |
| Wire Size                              | 32 – 28 AWG                   |
| Usage Conditions                       |                               |
| Operating Temperature Range            | -40 – 85 °C[-40 – 185 °F]     |
| Operation/Application                  |                               |
| Circuit Application                    | Power & Signal                |
|  |                               |
| Industry Standards                     |                               |
| Industry Standards<br>Glow Wire Rating | Standard Part - Not Glow Wire |

**C** For support call+1 800 522 6752

Housing, Receptacle, Wire-to-Board, 5 Position, .049 in [1.25 mm] Centerline, Crimp, 1 Row, Natural, Mating Retention, Wire & Cable, MIS



| Packaging Quantity                            | 1000  |
|---|---|
| Packaging Method                              | Bag/Carton  |
| Product Compliance                            |   |
| EU RoHS Directive 2011/65/EU                  | Compliant   |
| EU ELV Directive 2000/53/EC                   | Compliant   |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold   |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2023<br>(235)<br>Candidate List Declared Against: JUNE<br>2023 (235)<br>Does not contain REACH SVHC |
| Halogen Content                               | Low Halogen - Br, Cl, F, I < 900 ppm per<br>homogenous material. Also BFR/CFR/PVC<br>Free   |
| Solder Process Capability                     | Not applicable for solder process capability  |
|   |   |

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

### **Compatible Parts**




### Also in the Series | MIS

**C** For support call+1 800 522 6752

Housing, Receptacle, Wire-to-Board, 5 Position, .049 in [1.25 mm] Centerline, Crimp, 1 Row, Natural, Mating Retention, Wire & Cable, MIS





## Customers Also Bought



| 1.25mm WTB Socket,Housing,2p | 1.25mm WTB Socket,Housing,3p | RECEPT ASSY, 140 POS, VERT, SLIVER | 280 POS., CONNECTOR ASSEMBLY, |
|------------------------------|------------------------------|------------------------------------|-------------------------------|
|                              |                              | 2.0                                | SLIVER 2.0                    |
|                              |                              |                                    |                               |



### Documents

Product Drawings 1.25mm WTB Socket,Housing,5p

English

### **CAD** Files

Customer View Model

ENG\_CVM\_440146-5\_B.2d\_dxf.zip

English

Customer View Model

**S** For support call+1 800 522 6752

Housing, Receptacle, Wire-to-Board, 5 Position, .049 in [1.25 mm] Centerline, Crimp, 1 Row, Natural, Mating Retention, Wire & Cable, MIS



#### ENG\_CVM\_440146-5\_B.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_440146-5\_B.3d\_stp.zip

English

#### 3D PDF

English

Customer View Model

ENG\_CVM\_CVM\_440146-5\_B1.3d\_stp.zip

English

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_440146-5\_B1.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_440146-5\_B1.3d\_igs.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages HPI Connectors QRG

English

Product Specifications
Application Specification

English

Agency Approvals UL Report

English