SSRA-240D2R <


Potter & Brumfield | Potter & Brumfield SSRA

TE Internal #: 5-1393030-7 Power Relays, Solid State, 1 Form A (SPST-NO), Printed Circuit Board, Potter & Brumfield SSRA

View on TE.com >



Relays, Contactors & Switches > Relays > Power Relays > Solid State Relays, P&B SSRA Series



Power Relay Type: Solid State

Contact Arrangement: 1 Form A (SPST-NO)

Relay Mounting Type: Printed Circuit Board

All Solid State Relays, P&B SSRA Series (2)

Features

Product Type Features	
Output Type	AC
Power Relay Type	Solid State
Configuration Features	
Output Switching	Random
Electrical Characteristics	
Input Voltage Typical	4 – 10 VDC
Output Voltage (Max)	280 V
Output Voltage Rating (AC Relays)	12 – 280 Vrms
Output Current Rating	.06 – 2 Arms
Output Voltage Rating (DC Relays)	12 – 280 VDC
Output Current (Min)	.06 A
Insulation Initial Dielectric Between Contacts & Coil	2500 Vrms
Body Features	

Product Weight

4.3 g[.15 oz]

SSRA-240D2R

Power Relays, Solid State, 1 Form A (SPST-NO), Printed Circuit Board, Potter & Brumfield SSRA



Case Color	Black
Contact Features	
Switch Arrangement	1 Form A (SPST-NO)
Contact Arrangement	1 Form A (SPST-NO)
Termination Features	
Relay Termination Type	Printed Circuit Terminals
Mechanical Attachment	
Coupling	Optical
Relay Mounting Type	Printed Circuit Board
Housing Features	
Relay Housing Style	SIP
Dimensions	
Dimensions (L x W x H) (Approximate)	76.2 x 5.1 x 12.5 mm[.95 x .2 x .5 in]
Usage Conditions	
Operating Temperature Range	-30 – 80 °C
Operation/Application	
R-Switch & slimSSR Relays	Yes

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 260°C
Product Compliance Disclaimer	

SSRA-240D2R

Power Relays, Solid State, 1 Form A (SPST-NO), Printed Circuit Board, Potter & Brumfield SSRA



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | Potter & Brumfield SSRA



Power Relays	;(2)

Customers Also Bought



SSRA-240D2R

Power Relays, Solid State, 1 Form A (SPST-NO), Printed Circuit Board, Potter & Brumfield SSRA





Documents

CAD Files **Customer View Model**

ENG_CVM_CVM_5-1393030-7_A1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_5-1393030-7_A1.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_5-1393030-7_A1.2d_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the Terms and Conditions of use

Datasheets & Catalog Pages

8-1773454-1 SSRA Series 2A SIP Solid State Relay Data Sheet

English

SSRA_datasheet

English

Solid State Relay SSRA Series Data Sheet

English

Agency Approvals

UL

English