
TE Internal #: 5-1393127-5

Definite Purpose Contactors, 2, 24 VDC Coil Voltage, 20 A, Panel, Screw Terminal, 288  $\Omega$  Coil Resistance, 600 VAC Switching Voltage

View on TE.com >



Relays, Contactors & Switches > Contactors > Definite Purpose Contactors



Pole Configuration: 2

Definite Purpose Contactor Coil Voltage Rating: 24 VDC

Definite Purpose Contactor Contact Current Rating: 20 A

Definite Purpose Contactor Mounting Type: Panel

Terminal Configuration: Screw Terminal

### **Features**

### **Product Type Features**

Product Category	Electromechanical Relays
Product Type	Contactor
Product Classification	Relays - Contactors
Contactor Type	Definite Purpose
Terminal Configuration	Screw Terminal

### **Electrical Characteristics**

Actuating System	DC
Coil Voltage (Max)	24 VDC
Definite Purpose Contactor Coil Voltage Rating	24 VDC
Definite Purpose Contactor Coil Resistance	288 Ω
Definite Purpose Contactor Contact Switching Voltage (Max)	600 VAC

### **Contact Features**

Pole Configuration	2
Definite Purpose Contactor Contact Current Rating	20 A
Mechanical Attachment	

Panel

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

Definite Purpose Contactor Mounting Type



EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUL 2021 (219) SVHC > Threshold: Cadmium oxide (5.1% in Component Part) Article Safe Usage Statements: Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts



# Customers Also Bought





TE Part #DT06-12SD-EP06 PLG, 12P, BRN, N, SEAL RET, ENH KEY, CAP,D



TE Part #8-1393113-7 KUEP-11D15-24=KU-



TE Part #2331369-1 DET SW4.7X3.8X2.3 GW VERT. NO AG RL





TE Part #2329383-4 PB OFF/ON FC GRE M1 TERM. IP68



TE Part #2329383-5 PB OFF/ON FC BLU M1 TERM. IP68



GX518 1Pt100 W0.15 L5/D1.8mm





TE Part #ANT-916-SP Antenna SP PCB RPC 916MHz SMT

TE Part #04ZZXLF015 /HYB/2x22+/SH/PVC/UL2549/GY/-/

### **Documents**

### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_5-1393127-5\_C.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_5-1393127-5\_C.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_5-1393127-5\_C.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

## Datasheets & Catalog Pages

PRD 10 to 50 Amp Heavy Duty AC or DC Power Relay

English

**Product Specifications** 

Definite Purpose Contactors, 2, 24 VDC Coil Voltage, 20 A, Panel, Screw Terminal, 288  $\Omega$  Coil Resistance, 600 VAC Switching Voltage



# Definitions General Purpose Relays

English