# 5-146280-3 ACTIVE

#### AMPMODU | AMPMODU Headers

TE Internal #: 5-146280-3

PCB Mount Header, Vertical, Board-to-Board, 3 Position, 2.54 mm [. 1 in] Centerline, Breakaway, Gold, Through Hole - Solder, Signal,

AMPMODU Headers

View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles











PCB Connector Assembly Type: PCB Mount Header

PCB Mount Orientation: Vertical
Connector System: Board-to-Board

Number of Positions: 3

Number of Rows: 1

### **Features**

#### **Product Type Features**

PCB Connector Assembly Type	PCB Mount Header
Connector System	Board-to-Board
Header Type	Breakaway
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

#### **Configuration Features**

Connector Contact Load Condition	Fully Loaded
PCB Mount Orientation	Vertical
Number of Positions	3
Number of Rows	1
Board-to-Board Configuration	Parallel

### **Body Features**

Primary Product Color	Black	
Timary Troduct Color	Diddit	

#### **Contact Features**



Mating Square Post Dimension	.64 mm[.025 in]
	100 – 200 μin
PCB Contact Termination Area Plating Material Finish	Matte
Contact Shape & Form	Square
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin-Lead
Contact Base Material	Copper Alloy
Contact Mating Area Plating Material	Gold
Contact Mating Area Plating Material Thickness	.381 μm[15 μin]
Contact Type	Pin
Contact Current Rating (Max)	3 A
Termination Features	
Square Termination Post & Tail Dimension	.64 mm[.025 in]
Termination Post & Tail Length	3.05 mm[.12 in]
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
Mating Alignment	Without
PCB Mount Retention	Without
PCB Mount Alignment	Without
Connector Mounting Type	Board Mount
Housing Features	
Centerline (Pitch)	2.54 mm[.1 in]
Housing Material	LCP (Liquid Crystal Polymer), LCP-GF (Liquid Crystal Polymer)
Dimonsions	
Dimensions	
Dimensions  PCB Thickness (Recommended)	1.6 mm[.063 in]
	1.6 mm[.063 in]
PCB Thickness (Recommended)	1.6 mm[.063 in]  High
PCB Thickness (Recommended)  Usage Conditions	
PCB Thickness (Recommended)  Usage Conditions  Housing Temperature Rating	High
PCB Thickness (Recommended)  Usage Conditions  Housing Temperature Rating  Operating Temperature Range	High



Approved Standards	CSA LR7189, UL E28476
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Quantity	540
Packaging Type	Carton

#### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Pin-in-Paste capable to 260°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**





### Also in the Series | AMPMODU Headers



PCB Connector Mounting(1)



PCB Connector Shrouds(1)



PCB Headers & Receptacles(4872)



PCB Latches, Locks & Retainers(1)




Wire-to-Board Connector Assemblies & Housings(5)



Wire-to-Board Connector Contacts(65)

## Customers Also Bought



TE Part #5102153-5

A/L UNIV HDR 24P VERT



TE Part #7-1879233-7 SMW5 150R 5%



TE Part #5-146280-6 06 MODII HDR SRST B/A .100CL



TE Part #282847-4
TERMI-BLOK PCB MOUNT 35 4P.5



TE Part #8-1879213-9 CPF 0402 249R 0.1% 25PPM 1K RL



TE Part #202174-4
GUIDE SOC. ASSY. 104 CTR. FSTN



TE Part #1-2379397-7
MCIO INTERGRATED CONN, V/T,8X,
SMT TYPE



TE Part #1-640383-4 14P MTA156 HDR ASSY STR SQ SN

PCB Mount Header, Vertical, Board-to-Board, 3 Position, 2.54 mm [.1 in] Centerline, Breakaway, Gold, Through Hole - Solder, Signal, AMPMODU Headers



TE Part #2213871-3 LIGHT CONTROLLER BASE ASSY, 81MM DIA,7POS

#### **Documents**

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_5-146280-3\_D.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_5-146280-3\_D.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_5-146280-3\_D.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Environmental Compliance

MD\_5-146280-3\_04252018515\_dmtec

English

MD\_5-146280-3\_04252018515\_dmtec

English