AMP | LEAVYSEAL

TE Internal #: 5-1718323-1

Housing for Male Terminals, Wire-to-Wire, 39 Position, .197 in [5 mm] Centerline, Sealable, Green, Signal, Panel Mount, LEAVYSEAL

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > LEAVYSEAL Housings











Connector System: Wire-to-Wire

Number of Positions: 39

Connector & Housing Type: Housing for Male Terminals

Centerline (Pitch): 5 mm [.197 in]

Sealable: **Yes**

All LEAVYSEAL Housings (64)

Features

Product Type Features

| Product Type reatures | |
|----------------------------|----------------------------|
| Mixed & Hybrid Connector | No |
| Connector Shape | Rectangular |
| Connector System | Wire-to-Wire |
| Connector & Housing Type | Housing for Male Terminals |
| Sealable | Yes |
| Primary Locking Feature | On the Terminal |
| Configuration Features | |
| Number of Positions | 39 |
| Number of Rows | 3 |
| Electrical Characteristics | |
| Operating Voltage | 36 VDC |

12 V, 24 V

Nominal Voltage Architecture



| Cable Exit Angle | 90° |
|------------------------------|---|
| Primary Product Color | Green |
| Connector & Keying Code | E |
| Contact Features | |
| Contact Size | 2.8mm |
| Contact Type | Tab |
| Mating Tab Width | 2.8 mm[.11 in] |
| Contact Current Rating (Max) | 40 A |
| Mechanical Attachment | |
| Terminal Position Assurance | Yes |
| Strain Relief | With |
| Mating Alignment Type | Keyed |
| Mating Alignment | With |
| Connector Mounting Type | Panel Mount |
| Housing Features | |
| Housing Material | PBT GF |
| Centerline (Pitch) | 5 mm[.197 in] |
| Dimensions | |
| Connector Height | 45.8 mm[1.803 in] |
| Product Width | 70.7 mm[2.783 in] |
| Product Length | 113.25 mm[4.459 in] |
| Row-to-Row Spacing | 5.5 mm[.217 in] |
| Usage Conditions | |
| Operating Temperature (Max) | 70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C[158 °F][167 °F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F] |
| Operating Temperature Range | -40 – 120 °C[-40 – 248 °F] |
| Operation/Application | |
| Circuit Application | Signal |
| Industry Standards | |
| Degree of Protection | IP67, IP69K |
| UL Flammability Rating | UL 94HB |



Packaging Features

| Packaging Quantity | 80 |
|--------------------------------------|-----|
| Packaging Method | Box |
| Other | |
| Serviceable | Yes |
| Connector Position Assurance Capable | No |

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant |
|---|--|
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC |
| Halogen Content | BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources. |
| Solder Process Capability | Not applicable for solder process capability |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts
















Also in the Series | LEAVYSEAL







Automotive Housings(79)



Insertion & Extraction Tools(5)



Other Automotive Connector Accessories(15)



Customers Also Bought



















Documents

Product Drawings

2.8MM TAB HSG.,39POS.,ASSY

English

2.8MM TAB HSG.,39POS.,ASSY

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_5-1718323-1_D_c-5-1718323-1-d.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_5-1718323-1_D_c-5-1718323-1-d.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_5-1718323-1_D_c-5-1718323-1-d.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

ICT Terminals and Connectors Catalogue

English

Product Specifications

Application Specification

German