5-1971895-2 ACTIVE

RAST | RAST 5 IDC Connectors

TE Internal #: 5-1971895-2

PCB Mount Header, Vertical, Wire-to-Board, 2 Position, 5 mm [.197 in] Centerline, Fully Shrouded, Tin, Through Hole - Solder, RAST 5

IDC Connectors


View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles











Connector System: Wire-to-Board

Number of Positions: 2

Number of Rows: 1

Centerline (Pitch): 5 mm [.197 in]
PCB Mount Orientation: Vertical

Features

Product Type Features

Connector System	Wire-to-Board
Header Type	Fully Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
PCB Connector Assembly Type	PCB Mount Header
Configuration Features	
Keying & Polarized Position Locations	2D
Number of Columns	2
Number of Positions	2
Number of Rows	1
PCB Mount Orientation	Vertical
Electrical Characteristics	
Operating Voltage	250 VAC

Body Features



Primary Product Color	Natural
Contact Features	
PCB Contact Termination Area Plating Material Thickness	2 μm[78.74 μin]
Contact Layout	Inline
Mating Tab Width	6.3 mm[.248 in]
Mating Tab Thickness	.8 mm[.032 in]
Contact Underplating Material Thickness	1.27 μm[50 μin]
Contact Mating Area Plating Material Thickness	2 μm[78.74 μin]
PCB Contact Termination Area Plating Material Finish	Matte
Contact Shape & Form	Rectangular
Contact Mating Area Plating Material Finish	Matte
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Alloy
Contact Mating Area Plating Material	Tin
Contact Type	Tab
Contact Current Rating (Max)	16 A
Termination Features	
Square Termination Post & Tail Dimension	.8 mm[.032 in]
Termination Post & Tail Length	3.5 mm[.13 in]
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
PCB Mount Alignment Type	Polarizing Pegs
Mating Alignment Type	Keyed
Mating Retention	With
Mating Retention Type	Latch
Connector Mounting Type	Board Mount
Mating Alignment	With
PCB Mount Alignment	With
PCB Mount Retention	Without
Housing Features	
Housing Material	Nylon



Centerline (Pitch)	5 mm[.197 in]
Dimensions	
Connector Length	12.3 mm[.48 in]
Connector Height	12.8 mm[.5 in]
Connector Width	14.9 mm[.58 in]
Usage Conditions	
Operating Temperature Range	-40 – 120 °C[-40 – 248 °F]
Operation/Application	
Circuit Application	Power
Circuit Application Industry Standards	Power
	VL
Industry Standards	
Industry Standards Agency/Standard	UL
Industry Standards Agency/Standard Approved Standards	UL UL E28476
Industry Standards Agency/Standard Approved Standards UL Flammability Rating	UL UL E28476

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Out of Scope
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products



will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 2-1971845-2 2P, RAST 5 Tab Header, THV



TE Part # 3-1971845-2 2P, RAST 5 Tab Header, THV



TE Part # 6-1971895-2 2P, RAST 5 Tab Header, THV



TE Part # 1-1971845-2 2P, RAST 5 Tab Header, THV



TE Part # 1-1971895-2 2P, RAST 5 Tab Header, THV



TE Part # 2-1971895-2 2P, RAST 5 Tab Header, THV



TE Part # 3-1971895-2 2P, RAST 5 Tab Header, THV



TE Part # 4-1971845-2 2P, RAST 5 Tab Header, THV



TE Part # 4-1971895-2 2P, RAST 5 Tab Header, THV



TE Part # 5-1971845-2 2P, RAST 5 Tab Header, THV



TE Part # 6-1971845-2 2P, RAST 5 Tab Header, THV



Also in the Series | RAST 5 IDC Connectors



Automotive Terminals(8)



Connector Contacts(12)



Crimp Terminal Housings(41)



Insertion & Extraction Tools(1)





PCB Headers & Receptacles(417)



Rectangular Connector Housings(1)



Standard Edge Connectors(34)



Standard Rectangular Connectors(68)



Wire-to-Board Connector Assemblies & Housings(214)



Wire-to-Board Connector Contacts(2)


Customers Also Bought



TE Part #8-215079-6
Female-on-Board Connector, Top
Entry



TE Part #1-1415899-3 PCB Power Relay: 12-16 Amp, Monostable



TE Part #1939983-1 GIC3.3 HDR ASS'Y 10POS 2ROW



TE Part #1-188685-2 STD TIMER PCB CONTACT



TE Part #1-2299683-5
EP2.5 HDR 5P VERT W/O BOSS,
TAPING,RED



TE Part #4-1971798-2 NEW GI CONN2.5 HDR ASMBLY 4P BLU D1.0



TE Part #917723-4
2.5 SIGNAL D/LOCK HDR ASSY 3P



RA SMC2.5 Potting header_9P

Documents

Product Drawings

2P, RAST 5 Tab Header, THV

English

CAD Files

3D PDF

3D

Customer View Model ENG_CVM_CVM_5-1971895-2_B.2d_dxf.zip

PCB Mount Header, Vertical, Wire-to-Board, 2 Position, 5 mm [.197 in] Centerline, Fully Shrouded, Tin, Through Hole - Solder, RAST 5 IDC Connectors



English

Customer View Model

ENG_CVM_CVM_5-1971895-2_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_5-1971895-2_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Product Specification

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English

Agency Approvals

VDE Certificate

English