

RU73X1J10KLTFD

✓ ACTIVE

Holsworthy | Holsworthy RU73

TE Internal #: 5-2176269-3

10K Ω , Thin Film, Precision Resistor, .01 %, 2 Termination, 0603,
Taped & Reeled, .063 W, ± 3 ppm/ $^{\circ}\text{C}$, Solder, 1.55 x .8 x .45 mm,
Holsworthy RU73

[View on TE.com >](#)



Passive Components > Resistors > Surface Mount Resistors



Resistor Type: **Precision Resistor**
Number of Terminations: **2**
Package Size Code: **0603**
Packaging Method: **Taped & Reeled**
Passive Component Tolerance: **.01 %**

Features

Product Type Features

Product Type	Fixed Resistor
Resistor Type	Precision Resistor
Package Size Code	0603
Element Type	Thin Film

Configuration Features

Number of Resistors	1
---------------------	---

Electrical Characteristics

Voltage Rating	50 V
Passive Component Tolerance	.01 %
Resistance Class	1k Ω – 1M Ω
Resistance Value	10K Ω
Power Rating	.063 W

Termination Features

Number of Terminations	2
------------------------	---



Surface Mount Resistor Termination Type	Solder
---	--------

Dimensions

Passive Component Dimensions	1.55 x .8 x .45 mm
------------------------------	--------------------

Usage Conditions

Temperature Coefficient	± 3 ppm/ $^{\circ}\text{C}$
-------------------------	---------------------------------

Packaging Features

Packaging Method	Taped & Reeled
------------------	----------------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Reflow solder capable to 260 $^{\circ}\text{C}$

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

RU73X1J10KLTDF

10K Ω , Thin Film, Precision Resistor, .01 %, 2 Termination, 0603, Taped & Reeled, .063 W, ± 3 ppm/ $^{\circ}\text{C}$, Solder, 1.55 x .8 x .45 mm, Holsworthy RU73



TE Part # 5-2176267-9
RU 0603 100R 0.01% 2PPM 1K RL

TE Part # 7-2176267-6
RU 0603 150R 0.01% 2PPM 1K RL

Also in the Series | [Holsworthy RU73](#)

[Surface Mount Resistors\(757\)](#)

Customers Also Bought

TE Part #3-647502-6
06P MTA100 SMT ASSY,SN,TAPE, LF

TE Part #1676427-2
RN 0805 75K 0.1% 10PPM 1KRL

TE Part #1-770875-1
06P MINI UMNL HDR ASSY AU LF

TE Part #1622838-1
CRG0603 1% 12K

TE Part #8-1879338-2
CPF 0603 187K 1% 50PPM 1K RL

TE Part #2-2176345-0
CRGCQ 1210 390R 1%

Documents

Product Drawings

[RU 0603 10K 0.01% 2PPM 1K RL](#)

English

Datasheets & Catalog Pages

[Thin film chip resistor RU73 series](#)

English

RU73X1J10KLTDF

10K Ω , Thin Film, Precision Resistor, .01 %, 2 Termination, 0603, Taped & Reeled, .063 W, ± 3 ppm/ $^{\circ}$ C, Solder, 1.55 x .8 x .45 mm, Holsworthy RU73

