
RLC73K2BR215FTDF <

CGS | CGS RLC73 TE Internal #: 5-2176579-7 .215 Ω, Thick Film, Current Sensing Resistor, 1 %, 2 Termination, 1206, Taped & Reeled, .25 W, ±200 ppm/°C, Solder, 3.1 x 1.55 x .55 mm, CGS RLC73

View on TE.com >

Passive Components > Resistors > Surface Mount Resistors



Resistor Type: Current Sensing Resistor

Number of Terminations: 2

Package Size Code: 1206

Packaging Method: Taped & Reeled

Passive Component Tolerance: 1%

Features



Product Type Features

Product Type	Fixed Resistor
Resistor Type	Current Sensing Resistor
Package Size Code	1206
Element Type	Thick Film
Configuration Features	
Number of Resistors	1
Electrical Characteristics	
Passive Component Tolerance	1 %
Resistance Class	Up to 1kΩ
Resistance Value	.215 Ω
Power Rating	.25 W
Termination Features	
Number of Terminations	2
Surface Mount Resistor Termination Type	Solder

RLC73K2BR215FTDF

.215 Ω, Thick Film, Current Sensing Resistor, 1 %, 2 Termination, 1206, Taped & Reeled, .25 W, ±200 ppm/°C, Solder, 3.1 x 1.55 x .55 mm, CGS RLC73



Dimensions

Passive Component Dimensions	3.1 x 1.55 x .55 mm
Usage Conditions	
Operating Temperature Range	-55 – 155 °C
Temperature Coefficient	±200 ppm/°C
Packaging Features	
Packaging Method	Taped & Reeled

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Halogen Content

Solder Process Capability

Reflow solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts

RLC73K2BR215FTDF

.215 Ω, Thick Film, Current Sensing Resistor, 1 %, 2 Termination, 1206, Taped & Reeled, .25 W, ±200 ppm/°C, Solder, 3.1 x 1.55 x .55 mm, CGS RLC73





Also in the Series | CGS RLC73



Documents

Product Drawings RLC73K 2B R215 1% 1K RL

English

CAD Files

Customer View Model

ENG_CVM_CVM_5-2176579-7_BA.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_5-2176579-7_BA.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_5-2176579-7_BA.2d_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages SMD Low Ohmic - Current Sense Resistors - Type RLC73 Series

English