

### Ultra-Fast | Ultra-Fast 250

TE Internal #: 5-520183-2

Quick Disconnects, Receptacle, 22 – 18 AWG Wire Size, .32 – .82 mm<sup>2</sup> Wire Size, Mating Tab Width 6.35 mm [.25 in], Straight, Brass,

Ultra-Fast 250

View on TE.com >



Terminals & Splices > Quick Disconnects











Quick Disconnect Terminal Type: Receptacle

Wire Size: .32 – .82 mm<sup>2</sup>

Mating Tab Width: 6.35 mm [ .25 in ] Mating Tab Thickness: .81 mm [ .032 in ]

### **Features**

Product Type Features	
Terminal Features	Wire Stop
Insertion Force	Normal
Configuration Features	
Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire
Electrical Characteristics	
Voltage Rating	600 V
Body Features	
Insulation Material	Nylon
Contact Features	
Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]

.81 mm[.032 in]

Straight

Mating Tab Thickness

Terminal Orientation



Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Closed
Termination Features	
Product Terminates To	Wire & Cable
Mechanical Attachment	
Wire Insulation Support	With
Mating Retention Type	Dimple
Dimensions	
Terminal Material Thickness	.41 mm[.016 in]
Product Length	21.75 mm[.856 in]
Compatible Insulation Diameter Range	3.43 mm[.135 in]
Wire Size	.32 – .82 mm²
Usage Conditions	
Insulation Option	Fully Insulated
Operating Temperature Range	-40 - 110 °C[-40 - 230 °F]
Industry Standards	
Agency/Standard	UL
UL Flammability Rating	UL 94V-2
Packaging Features	
Packaging Quantity	2200
Packaging Method	Strip/Reel
Other	
Barrel Color	Red

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	



Current ECHA Candidate List: JUNE 2023

(235)

Candidate List Declared Against: JUNE

2023 (235)

Does not contain REACH SVHC

Halogen Content

Low Halogen - Br, Cl, F, I < 900 ppm per
homogenous material. Also BFR/CFR/PVC
Free


Solder Process Capability

Not applicable for solder process capability

### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**














Also in the Series | Ultra-Fast 250

Quick Disconnects, Receptacle, 22 – 18 AWG Wire Size, .32 – .82 mm² Wire Size, Mating Tab Width 6.35 mm [.25 in], Straight, Brass, Ultra-Fast 250






Automotive Connector Caps & Covers (1)



Automotive Housings(6)



Quick Disconnects(49)

# Customers Also Bought


















TE Part #2226000-1 ASSEMBLY,SOCKET,M-USB CONN.

## **Documents**

**Product Drawings** 

ULTRA-FAST 250 ASY REC 22-18 AWG TPBR

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_5-520183-2\_V.2d\_dxf.zip

Quick Disconnects, Receptacle, 22 – 18 AWG Wire Size, .32 – .82 mm² Wire Size, Mating Tab Width 6.35 mm [.25 in], Straight, Brass, Ultra-Fast 250



English

**Customer View Model** 

ENG\_CVM\_CVM\_5-520183-2\_V.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_5-520183-2\_V.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

**Product Specifications** 

**Application Specification** 

English

**Product Environmental Compliance** 

**Product Compliance Document** 

English

**Product Compliance Document** 

English