SOLISTRAND

TE Internal #: 50334-3

Closed Ring Tongue Terminal, 26 – 22 AWG, M2 / #2 Stud Size,


2.18 mm [.086 in] Stud Diameter, Closed Barrel, Straight, Unplated,

Uninsulated

View on TE.com >



Terminals & Splices > Ring Terminals



Ring Terminal Product Type: Closed Ring Tongue Terminal

Wire Size: **202 – 810 CMA**

Stud Size: #2, M2

Features

Product Type Features

Ring Terminal Product Type	Closed Ring Tongue Terminal
Stud Size	#2, M2
Sealable	No
Wire Insulation Support Retention Type	Non-Insulation Support
Configuration Features	
Number of Holes	1
Body Features	
Product Weight	.126 g
Contact Features	
Barrel Type	Closed
Terminal Orientation	Straight
Terminal Plating Material	Unplated
Mechanical Attachment	
Wire Insulation Support	Without



Stud Diameter 2.18 mm[.086 in] Tongue Thickness .79 mm[.031 in]	Wire Size	202 – 810 CMA
	Stud Diameter	2.18 mm[.086 in]
Due also et la constle	Tongue Thickness	.79 mm[.031 in]
Product Length 10.64 mm[.419 in]	Product Length	10.64 mm[.419 in]
Barrel Inside Diameter .79 mm[.031 in]	Barrel Inside Diameter	.79 mm[.031 in]

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	170 °C[338 °F]

Operation/Application

Compatible With Wire Base Material	Copper
Compatible With Wire Plating Material	Tin

Industry Standards

Packaging Features

Packaging Quantity	1000
Packaging Method	Loose Piece

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these



limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought





















Documents



Product Drawings

SOLIS,RING,26-22,2,UNPLTD

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_50334-3_L.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_50334-3_L.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_50334-3_L.3d_stp.zip

English

Customer View Model

ENG_CVM_50334-3_H1.3d_igs.zip

English

Customer View Model

ENG_CVM_50334-3_H1.3d_stp.zip

English

Customer View Model

ENG_CVM_50334-3_H1.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

SOLISTRAND - QRG

English