

STRATO-THERM

TE Internal #: 50832-2


Closed Ring Tongue Terminal, 22 – 20 AWG, M4 / #8 Stud Size, 4.34 mm [.171 in] Stud Diameter, Closed Barrel, Straight, Nickel,

STRATO-THERM

View on TE.com >



Terminals & Splices > Ring Terminals



Ring Terminal Product Type: Closed Ring Tongue Terminal

Wire Size: **509 – 1290 CMA**

Stud Size: #8, M4

Features

Product Type Features

Ring Terminal Product Type	Closed Ring Tongue Terminal
Stud Size	#8, M4
Sealable	No
Wire Insulation Support Retention Type	Insulation Support
Configuration Features	
Number of Holes	1
Electrical Characteristics	
Voltage Rating	300 V
Contact Features	
Barrel Type	Closed
Terminal Orientation	Straight
Terminal Plating Material	Nickel
Mechanical Attachment	
Wire Insulation Support	With



Wire Size	509 – 1290 CMA
Stud Diameter	4.34 mm[.171 in]
Tongue Thickness	.79 mm[.031 in]
Product Length	21.2 mm[.835 in]
Compatible Insulation Diameter (Max)	2.54 mm[.1 in]
Compatible Insulation Diameter Range	.89 – 2.54 mm[.035 – .1 in]
Usage Conditions	
Insulation Option	Partially Insulated
Operating Temperature Range	288 °C[550 °F]
Industry Standards	
Government Qualified Terminal	No
Packaging Features	
Packaging Quantity	1000

Tape Mounted

Product Compliance

Packaging Method

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits



as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


Compatible Parts





Also in the Series | STRATO-THERM







Customers Also Bought



















TE Part #148032-000
MTCST-YH1-P03

TE Part #C02560-000
MTCST-YH2-P03

Documents

Product Drawings

TERMINAL, PIDG PTFE R 22-20 8

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_50832-2_H.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_50832-2_H.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_50832-2_H.3d_stp.zip

English

3D PDF

English

Customer View Model

ENG_CVM_50832-2_H1.3d_igs.zip

English

Customer View Model

ENG_CVM_50832-2_H1.3d_stp.zip

English

Customer View Model

ENG_CVM_50832-2_H1.2d_dxf.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English

Product Environmental Compliance

TE Material Declaration

English

Closed Ring Tongue Terminal, 22 – 20 AWG, M4 / #8 Stud Size, 4.34 mm [.171 in] Stud Diameter, Closed Barrel, Straight, Nickel, STRATO-THERM

