

#### STRATO-THERM

TE Internal #: 50845

Closed Ring Tongue Terminal, 12 – 10 AWG, #6 / M3.5 Stud Size, 3.68 mm [.145 in] Stud Diameter, Closed Barrel, Straight, Nickel,

STRATO-THERM

View on TE.com >



Terminals & Splices > Ring Terminals



Ring Terminal Product Type: Closed Ring Tongue Terminal

Wire Size: 5180 – 13100 CMA

Stud Size: **#6, M3.5** 

### **Features**

### **Product Type Features**

Troduct Type reatures	
Ring Terminal Product Type	Closed Ring Tongue Terminal
Stud Size	#6, M3.5
Sealable	No
Wire Insulation Support Retention Type	Insulation Support
Configuration Features	
Number of Holes	1
Electrical Characteristics	
Voltage Rating	300 V
Body Features	
Product Weight	2.552 g
Contact Features	
Barrel Type	Closed
Terminal Orientation	Straight
Terminal Plating Material	Nickel



Wire Insulation Support	With
Dimensions	
Wire Size	5180 – 13100 CMA
Stud Diameter	3.68 mm[.145 in]
Tongue Thickness	1.07 mm[.042 in]
Product Length	27.51 mm[1.083 in]
Compatible Insulation Diameter (Max)	5.44 mm[.214 in]
Compatible Insulation Diameter Range	2.59 – 5.44 mm[.102 – .214 in]
Usage Conditions	
Insulation Option	Partially Insulated
Operating Temperature Range	288 °C[550 °F]
Industry Standards	
Government Qualified Terminal	No
Packaging Features	
Packaging Quantity	500
Packaging Method	Loose Piece

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these



limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts





## Also in the Series | STRATO-THERM



Crimp Wire Pins, Tabs & Ferrules(1)



Ring Terminals(93)



Splices(16)

# Customers Also Bought













TE Part #ZPF000000000008593 983-6S 12-12 SN-L



TE Part #1577640-1 TERMINAL RT PIDG PEEK STRATO 14-12 AWG



TE Part #ZPF000000000007414 983-0S 18-31 SN-L



TE Part #ZPF00000000003618
724-0904-22



### **Documents**

### **Product Drawings**

TERMINAL, PIDG PTFE R 12-10 6

English

### **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_50845\_K.2d\_dxf.zip

English

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_50845\_K.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_50845\_K.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

### Datasheets & Catalog Pages

STRATO-THERM Terminals & Splices for High Temperature Applications

English

### **Product Specifications**

**Application Specification** 

English