# 5120779-1 ✓ ACTIVE

## Z-PACK | Z-PACK 2mm HM

TE Internal #: 5120779-1

Hard Metric Backplane Connectors, PCB Mount Header, ≤1 Gb/s, 12 Column, 12 Row, Mezzanine, 144 Position, 1.5 mm [.059 in]

Centerline, Z-PACK 2mm HM

View on TE.com >




Connectors > PCB Connectors > Backplane Connectors > Hard Metric Backplane Connectors >


Hard Metric Male Connector: Traditional Backplane, Mezzanine, 2mm











PCB Connector Assembly Type: PCB Mount Header

Data Rate: ≤1 Gb/s

Number of Columns: 12

Number of Rows: 12

Backplane Architecture: Mezzanine

All Hard Metric Male Connector: Traditional Backplane, Mezzanine, 2mm (124)

## **Features**

## **Product Type Features**

Backplane Interface Type	2mm HM
PCB Connector Assembly Type	PCB Mount Header
Connector System	Board-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

## **Configuration Features**

Rows Loaded	Fully Loaded
Number of Columns	12
Number of Rows	12
Backplane Architecture	Mezzanine
Number of Positions	144
PCB Mount Orientation	Vertical



## Signal Characteristics

Crosstalk Version	Reduced
Data Rate	≤1 Gb/s

## **Body Features**

Primary Product Color	Black	
Timary Troduct Color	Brack	

#### **Contact Features**

Contact Mating Area Length	8.2 mm
Feedthrough Post Length	3.7 mm
CompactPCI Designation	None
Contact Type	Pin
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Phosphor Bronze
Contact Mating Area Plating Material	Nickel
Contact Mating Area Plating Material Thickness	.76 μm[30 μin]
Contact Current Rating (Max)	.7 A

#### **Termination Features**

Termination Method to Printed Circuit Board	Through Hole - Press-Fit	

## Mechanical Attachment

Front Mating Level	Level 2
Connector Mounting Type	Board Mount

## **Housing Features**

Housing Material	Polyester - GF
Centerline (Pitch)	1.5 mm[.059 in]

#### **Dimensions**

Backplane Module Length		23.9 mm
-------------------------	--	---------

## **Usage Conditions**

Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
-----------------------------	----------------------------

## Operation/Application

Shielded	No
Circuit Application	Signal



## **Industry Standards**

UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Quantity	20
Packaging Method	Tube

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## **Compatible Parts**





## Also in the Series | Z-PACK 2mm HM



Backplane Coding Keys(60)



Backplane Connector Housings(4)



Backplane Guide Hardware(37)



Backplane Power Connectors(6)



Board-to-Board Connector Contacts(2)



Connector Caps & Covers(62)



Hard Metric Backplane Connectors (269)



High Speed Backplane Connectors(1)



Insertion & Extraction Tools(2)



Rectangular Power Connectors(87)

# Customers Also Bought





















## **Documents**

## **Product Drawings**

2MMHM HDR ASY,12R SEL/LD 144 P

English

#### **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_5120779-1\_O.2d\_dxf.zip

English

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_5120779-1\_O.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_5120779-1\_O.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## **Product Specifications**

**Application Specification** 

English