

### **SOLISTRAND**

TE Internal #: 52705-1


Spring Spade Terminal, 16 – 14 AWG, #10 Stud Size, 4.82 mm [.19

in] Stud Diameter, Closed Barrel, Straight, Tin, Uninsulated

View on TE.com >



Terminals & Splices > Spade Terminals



Spade Terminal Type: Spring Spade Terminal

Wire Size: 2050 – 5180 CMA

Stud Size: #10

## **Features**

## **Product Type Features**

Stud Size	#10
Sealable	No
Wire Insulation Support Retention Type	Non-Insulation Support

## **Contact Features**

Spade Terminal Type	Spring Spade Terminal
Barrel Type	Closed
Terminal Orientation	Straight
Terminal Plating Material	Tin

## Mechanical Attachment

Wiedrianical Attachment	
Wire Insulation Support	Without
Dimensions	
Wire Size	2050 – 5180 CMA
Stud Diameter	4.82 mm[.19 in]
Tongue Thickness	.79 mm[.031 in]
Product Length	19.86 mm[.782 in]
Barrel Inside Diameter	2.26 mm[.089 in]



## **Usage Conditions**

Insulation Option	Uninsulated
Operating Temperature Range	170 °C[338 °F]
Operation/Application	
Compatible With Wire Base Material	Copper
Compatible With Wire Plating Material	Tin
Industry Standards	
Government Qualified Terminal	No
Packaging Features	
Packaging Quantity	1000
Packaging Method	Loose Piece
Other	

Budget

# **Product Compliance**

Line

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides



on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts



# Customers Also Bought





# **Documents**

## **Product Drawings**

**BUDGET SPRING SPADE 16-14 10** 

English

# CAD Files

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_52705-1\_R.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_52705-1\_R.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_52705-1\_R.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

### **Instruction Sheets**

Instruction Sheet (U.S.)

Spring Spade Terminal, 16 – 14 AWG, #10 Stud Size, 4.82 mm [.19 in] Stud Diameter, Closed Barrel, Straight, Tin, Uninsulated



English

Agency Approvals

**UL Report** 

English