TE Internal #: 52931-1

Spring Spade Terminal, 22 – 16 AWG, #10 Stud Size, 4.82 mm [.19

in] Stud Diameter, Closed Barrel, Straight, Tin, Partially Insulated

View on TE.com >



Terminals & Splices > Spade Terminals > PIDG Short Spring Spade Tongue Terminals











Spade Terminal Type: Spring Spade Terminal

Wire Size: **509 – 3260 CMA** 

Stud Size: #10

All PIDG Short Spring Spade Tongue Terminals (38)

### **Features**

### **Product Type Features**

| Stud Size                              | #10                |
|--|--------------------|
| Sealable                               | No                 |
| Wire Insulation Support Retention Type | Insulation Support |
| Electrical Characteristics             |                    |
| Voltage Rating                         | 300 V              |
| Body Features                          |                    |
| Insulation Sleeve Color                | Red                |

### **Contact Features**

Stripe Color

| Spade Terminal Type       | Spring Spade Terminal |
|---------------------------|-----------------------|
| Barrel Type               | Closed                |
| Terminal Orientation      | Straight              |
| Terminal Plating Material | Tin                   |

Red

#### Mechanical Attachment

| Wire Insulation Support | With |  |
|-------------------------|------|--|



#### **Dimensions**

| Wire Size                            | 509 – 3260 CMA                |
|--------------------------------------|-------------------------------|
| Stud Diameter                        | 4.82 mm[.19 in]               |
| Tongue Thickness                     | .79 mm[.031 in]               |
| Product Length                       | 23.1 mm[.908 in]              |
| Compatible Insulation Diameter (Max) | 3.18 mm[.125 in]              |
| Compatible Insulation Diameter Range | 2.03 – 3.18 mm[.08 – .125 in] |

## **Usage Conditions**

| Insulation Option           | Partially Insulated |
|-----------------------------|---------------------|
| Operating Temperature Range | 105 °C[221 °F]      |

### Operation/Application

| Compatible With Wire Base Material    | Copper |
|---------------------------------------|--------|
| Compatible With Wire Plating Material | Tin    |

## **Industry Standards**

| Government Qualified Terminal | No |  |
|-------------------------------|----|--|
|-------------------------------|----|--|

## **Packaging Features**

| Packaging Quantity | 5000         |
|--------------------|--------------|
| Packaging Method   | Tape Mounted |

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Compliant   |
|---|---|
| EU ELV Directive 2000/53/EC                   | Compliant   |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold   |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC |
| Halogen Content                               | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free                                       |
| Solder Process Capability                     | Not applicable for solder process capability  |

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts













# Customers Also Bought





















### **Documents**

### **Product Drawings**

TERMINAL, PIDG SPR SPD 22-16 10

English

### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_52931-1\_S.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_52931-1\_S.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_52931-1\_S.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### **Product Specifications**

**Application Specification** 

English

### **Product Environmental Compliance**

MD\_52931-1\_10282017044\_dmtec

English

MD\_52931-1\_10282017044\_dmtec

English

Spring Spade Terminal, 22 – 16 AWG, #10 Stud Size, 4.82 mm [.19 in] Stud Diameter, Closed Barrel, Straight, Tin, Partially Insulated



### **Instruction Sheets**

AMP\* PIDG\* (VINYL) & PLASTI-GRIP\* SHORT SPRING SPADE TERMINALS FOR BAR

English

Instruction Sheet (U.S.)

English

Agency Approvals

**UL Report** 

English