

Z-PACK | Z-PACK 2mm HM

TE Internal #: 5352115-1 Hard Metric Backplane Connectors, PCB Mount Receptacle, ≤1 Gb /s, 11 Column, 5 Row, Mezzanine, 55 Position, 2 mm [.078 in] Centerline, Z-PACK 2mm HM

View on TE.com >

Connectors > PCB Connectors > Backplane Connectors > Hard Metric Backplane Connectors >

HM Receptacle Connector: Traditional Backplane, Coplanar, 2mm



PCB Connector Assembly Type: PCB Mount Receptacle

Data Rate: **≤1 Gb/s**

Number of Columns: 11

Number of Rows: 5

Backplane Architecture: Mezzanine

All HM Receptacle Connector: Traditional Backplane, Coplanar, 2mm (48)



Features

Product Type Features

Backplane Interface Type	2mm HM		
Ground Feature Type	Ground Return Shielding		
PCB Connector Assembly Type	PCB Mount Receptacle		
Connector System	Board-to-Board		
Sealable	No		
Connector & Contact Terminates To	Printed Circuit Board		
Configuration Features			
Mating & Unmating Configuration	Make First / Break Last		
Rows Loaded	A, B, C, D, E		
Number of Signal Positions			
Number of Signal Positions	55		
Number of Columns	55 11		

Hard Metric Backplane Connectors, PCB Mount Receptacle, ≤1 Gb/s, 11 Column, 5 Row, Mezzanine, 55 Position, 2 mm [.078 in] Centerline, Z-PACK 2mm HM



Backplane Architecture	Mezzanine
Number of Positions	55
PCB Mount Orientation	Right Angle
Signal Characteristics	
Crosstalk Version	Standard
Data Rate	≤1 Gb/s
Body Features	
Primary Product Color	Gray
Contact Features	
Feedthrough Post Length	3.7 mm
CompactPCI Designation	None
Contact Type	Socket
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Phosphor Bronze
Contact Mating Area Plating Material	Gold
Contact Mating Area Plating Material Thickness	1.27 μm[50 μin]
Contact Current Rating (Max)	1.5 A
Termination Features	
Termination Method to Printed Circuit Board	Through Hole - Press-Fit
Mechanical Attachment	
Mating Alignment Type	Multi-Purpose Center
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	PBT GF
Centerline (Pitch)	2 mm[.078 in]
Dimensions	
Backplane Module Length	25 mm
Usage Conditions	
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]

L For support call+1 800 522 6752

Hard Metric Backplane Connectors, PCB Mount Receptacle, ≤1 Gb/s, 11 Column, 5 Row, Mezzanine, 55 Position, 2 mm [.078 in] Centerline, Z-PACK 2mm HM



Shielded	Yes
Circuit Application	Power & Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Quantity	11
Packaging Method	Tube
Other	
Backplane Connector Comment	Female connector with pre-installed shield
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235)

2023 (235) Does not contain REACH SVHC

Not Low Halogen - contains Br or Cl > 900 ppm.

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

Halogen Content

Solder Process Capability

Hard Metric Backplane Connectors, PCB Mount Receptacle, ≤1 Gb/s, 11 Column, 5 Row, Mezzanine, 55 Position, 2 mm [.078 in] Centerline, Z-PACK 2mm HM





Also in the Series Z-PACK 2mm HM



Board-to-Board Connector Contacts(2)	Hard Metric Backplane Connectors (269)	High Speed Backplane Connectors(1)	Insertion & Extraction Tools(2)
PCB Connector Covers(4)	PCB Connector Shrouds(39)	PCB Ferrules & Shields(19)	Rectangular Power Connectors(87)

Customers Also Bought



Hard Metric Backplane Connectors, PCB Mount Receptacle, ≤1 Gb/s, 11 Column, 5 Row, Mezzanine, 55 Position, 2 mm [.078 in] Centerline, Z-PACK 2mm HM



3 5 6 7 5 6 7			
TE Part #6-100526-3 CODING DEV INSRT COLOR ORANGE	TE Part #1-2344141-1 IMP100S,R,RA5P16C,LG,39,TRAY PKG	TE Part #2005801-1 M-ZIF CONN. PLUG 260P SOLDER TYPE	TE Part #2344142-1 IMP100S,R,RA5P16C,UG,39,TRAY PKG

Documents

CAD Files

3D PDF

English

Customer View Model

ENG_CVM_5352115-1_G3.3d_igs.zip

English

Customer View Model

ENG_CVM_5352115-1_G3.3d_stp.zip

English

Customer View Model

ENG_CVM_5352115-1_G3.2d_dxf.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use

Product Specifications

Application Specification

English

Product Environmental Compliance MD_5352115-1_06142018840_dmtec

English

MD_5352115-1_06142018840_dmtec

English