TE Internal #: 5413515-2

BNC RF Interface, Jack, 50 Ω , Bayonet, 1 GHz Operating

Frequency, Cable-to-Panel / Cable-to-Board, 1 Position, Printed

Circuit Board, Panel Mount

View on TE.com >




Connectors > RF Connectors > Coax Connectors











RF Interface: BNC

RF Connector Style: Jack

RF Connector Mated Outer Diameter (Approximate): 14.53 mm [.572 in]

Impedance: 50Ω

RF Connector Coupling Mechanism: Bayonet

Features

Product Type Features

RF Interface	BNC
RF Connector Style	Jack
Connector System	Cable-to-Board, Cable-to-Panel
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Positions	1
Number of Coaxial Contacts	1

Electrical Characteristics

Impedance	50 Ω
-----------	------

Body Features

Body Material	Zinc
Body Plating Material	Nickel

Contact Features



RF Connector Center Contact Underplating Material	Nickel
	30 μin
RF Connector Center Contact Plating Material	Gold
RF Connector Center Contact Material	Phosphor Bronze
Termination Features	
Termination Post & Tail Length	3.43 mm[.135 in]
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
PCB Mount Retention	With
Panel Mount Feature Type	Lockwasher and Nut
RF Connector Coupling Mechanism	Bayonet
Connector Mounting Type	Panel Mount
RF Contact Captivation Method	Mechanical
Detent	With
Dimensions	
Dimensions Mounting Post Length	4.01 mm[.158 in]
	4.01 mm[.158 in] 13.18 mm[.519 in]
Mounting Post Length	
Mounting Post Length Profile Height from PCB	13.18 mm[.519 in]
Mounting Post Length Profile Height from PCB RF Connector Mated Outer Diameter (Approximate)	13.18 mm[.519 in]
Mounting Post Length Profile Height from PCB RF Connector Mated Outer Diameter (Approximate) Usage Conditions	13.18 mm[.519 in] 14.53 mm[.572 in]
Mounting Post Length Profile Height from PCB RF Connector Mated Outer Diameter (Approximate) Usage Conditions Operating Temperature Range	13.18 mm[.519 in] 14.53 mm[.572 in]
Mounting Post Length Profile Height from PCB RF Connector Mated Outer Diameter (Approximate) Usage Conditions Operating Temperature Range Operation/Application	13.18 mm[.519 in] 14.53 mm[.572 in] -55 – 85 °C[-67 – 185 °F]
Mounting Post Length Profile Height from PCB RF Connector Mated Outer Diameter (Approximate) Usage Conditions Operating Temperature Range Operation/Application Operating Frequency	13.18 mm[.519 in] 14.53 mm[.572 in] -55 – 85 °C[-67 – 185 °F]
Mounting Post Length Profile Height from PCB RF Connector Mated Outer Diameter (Approximate) Usage Conditions Operating Temperature Range Operation/Application Operating Frequency Packaging Features	13.18 mm[.519 in] 14.53 mm[.572 in] -55 – 85 °C[-67 – 185 °F] 1 GHz
Mounting Post Length Profile Height from PCB RF Connector Mated Outer Diameter (Approximate) Usage Conditions Operating Temperature Range Operation/Application Operating Frequency Packaging Features Packaging Method	13.18 mm[.519 in] 14.53 mm[.572 in] -55 – 85 °C[-67 – 185 °F] 1 GHz
Mounting Post Length Profile Height from PCB RF Connector Mated Outer Diameter (Approximate) Usage Conditions Operating Temperature Range Operation/Application Operating Frequency Packaging Features Packaging Method Other	13.18 mm[.519 in] 14.53 mm[.572 in] -55 - 85 °C[-67 - 185 °F] 1 GHz Tube

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions



China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





TE Part # CAT-076-BNCJKSH50 BNC RF Connector: jack assembly short, 50 Ohm, 4Ghz

















TE Part # 5228979-7

JACK,COML,SERIES BNC,GOLD PL



TE Part # 5228980-6

JACK,BHD,COML,SERIES BNC,GOLD



TE Part # 5227079-5 COMM BNC PLUG



TE Part # 5227079-6 COMM. BNC-PLUG



TE Part # 8-5227079-2 COMM BNC PLUG



TE Part # 1-5227079-1 COMM BNC PLUG



TE Part # 228979-7

JACK,COML,SERIES BNC,GOLD PL



TE Part # 413779-3 COML BNC,50 OHM, HEX CRIMP



TE Part # 5228980-7

JACK,BHD,COML,SERIES BNC,GOLD



TE Part # 228979-6

JACK,COML,SERIES BNC,GOLD PL



TE Part # 228980-6 JACK,BHD,COML,SERIES BNC,GOLD



TE Part # 228980-7 JACK,BHD,COML,SERIES BNC,GOLD

Customers Also Bought



TE Part #6609104-7 PE0SSSSX0=C1132




TE Part #5227161-9 RTANG JACK W/MTG PINS,BNC PCB



TE Part #8-215460-2 MICRO-MATCH FSID P



TE Part #5787617-2 RECP ASSY, R/A, STACKED, THRU-HOLE, USB,



TE Part #1-100317-5
DUAL LOADED



TE Part #354096-E SMCB 32 M AB VV 7-03 CL * 0007 137 E004



TE Part #1878647-3 MQC555GR







TE Part #454998-E MSPEED 83 F SMD F8 BE A-G 9999 137 094 *

Documents

CAD Files

3D PDF

English

Customer View Model

ENG_CVM_5413515-2_C.2d_dxf.zip

English

Customer View Model

ENG_CVM_5413515-2_C.3d_igs.zip

English

Customer View Model

ENG_CVM_5413515-2_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

Decoupled Connectors

English

Product Specifications

PCB Decoupled BNC Straight & Right Angle Jacks

English

Product Specification

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English