TE Internal #: 5555248-1

RJ45 Connectors, RJ45, Single Port, 1 x 1, RJ Type Jacks & Plugs, Standard Connector Contact Density, Jack, Cat 3, Standard - Latch

Down, 8 Position


View on TE.com >



#### Connectors > Modular Jacks & Plugs > RJ45 Connectors











Modular Jack & Plug Interface Type: RJ45

Port Configuration: Single Port
Port Matrix Configuration: 1 x 1

Modular Jacks & Plugs Products: RJ Type Jacks & Plugs

Connector Contact Density: Standard

#### **Features**

## Product Type Features

Connector Product Type	Connector Assembly
Modular Jack & Plug Interface Type	RJ45
Modular Jacks & Plugs Products	RJ Type Jacks & Plugs
Modular Connector Style	Jack
Grounding Options	None
Connector & Contact Terminates To	Printed Circuit Board

## **Configuration Features**

Status Indicator Type	None
Port Configuration	Single Port
Port Matrix Configuration	1 x 1
Connector Contact Density	Standard
Number of Positions	8
Number of Loaded Positions	8
PCB Mount Orientation	Right Angle

## **Body Features**



Modular Jack Latch Orientation	Standard - Latch Down
Connector Profile	Low
Contact Features	
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Current Rating (Max)	.2 A, 1.5 A
Contact Mating Area Plating Material	Gold
Contact Base Material	Phosphor Bronze
Contact Mating Area Plating Material Thickness	1.27 μm[50 μin]
Termination Features	
Termination Method to Printed Circuit Board	Surface Mount
Termination Post & Tail Length	3.56 mm[.14 in]
Mechanical Attachment	
Panel Mount Feature	With
Panel Mount Feature Type	Panel Stops
Connector Mounting Type	Panel Mount
Housing Features	
Mating Entry Location	Side
Centerline (Pitch)	1.02 mm[.04 in]
Housing Color	Black
Housing Material	High Temperature Nylon
Dimensions	
PCB Thickness (Recommended)	1.57 mm[.062 in]
Connector Height	12.7 mm[.5 in]
Usage Conditions	
Operating Temperature Range	-40 - 85 °C[-40 - 185 °F]
Operation/Application	
Shielded	No
Circuit Application	Signal
Industry Standards	
UL Flammability Rating	UL 94V-0



Performance Category Cat 3

#### **Packaging Features**

Pac	kaging Method	Box & Tray, Package
	8 8	<i>y.</i>

## **Product Compliance**


For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Reflow solder capable to 260°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**




# **Customers Also Bought**





TE Part #3-644486-0 10P MTA100 SHRDED HDR ASSY SN



TE Part #1-5499374-0 A/L UNIV HDR 50P VERT SHT LAT



TE Part #5-104935-3 03 MTE HDR SRRA LATCH



TE Part #280520-1 12P AMPMODU II SHRD HDR, ST, TIN



TE Part #5-102202-1 04 MODII HDR SRST SHRD LF




TE Part #5-146257-3 06 MODII HDR DRST B/A .100CL LF



TE Part #1-84953-6 1MM FPC HORZ.TOP CONT.ASSY 16P



TE Part #2307815-6
6P,2MM,BB,REC,SRVT,SMD,AU.76,TR,
W/CP



TE Part #282851-4
TERMI-BLOK PCB MOUNT 180 4P.5



TE Part #5415322-2 SURFACE MOUNT JACK, F SERIES

#### **Documents**

**Product Drawings** 

MJ,LPF,R/A,8P/8C,SMT,PNL STOP

English

**CAD Files** 

3D PDF

English

**Customer View Model** 

ENG\_CVM\_5555248-1\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_5555248-1\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_5555248-1\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

**Product Specifications** 

RJ45 Connectors, RJ45, Single Port, 1 x 1, RJ Type Jacks & Plugs, Standard Connector Contact Density, Jack, Cat 3, Standard - Latch Down, 8 Position



**Application Specification** 

English

**Application Specification** 

English