TE Internal #: 6-1393127-9

Definite Purpose Contactors, 2, 120 VAC Coil Voltage, 30 A, Panel,

1 Form X, SPST-NO-DM, Screw Terminal, 290 Ω Coil Resistance

View on TE.com >



Relays, Contactors & Switches > Contactors > Definite Purpose Contactors



Pole Configuration: 2

Definite Purpose Contactor Coil Voltage Rating: 120 VAC

Definite Purpose Contactor Contact Current Rating: 30 A

Definite Purpose Contactor Mounting Type: Panel

Definite Purpose Contactor Contact Arrangement: 1 Form X, SPST-NO-DM

Features

Product Type Features

Product Category	Electromechanical Relays
Product Type	Contactor
Product Classification	Relays - Contactors
Contactor Type	Definite Purpose
Terminal Configuration	Screw Terminal

Electrical Characteristics

Actuating System	AC
Coil Voltage (Max)	120 VAC
Definite Purpose Contactor Coil Voltage Rating	120 VAC
Definite Purpose Contactor Coil Resistance	290 Ω
Definite Purpose Contactor Contact Switching Voltage (Max)	600 VAC

Contact Features

Contact Base Material	Silver Cadmium Oxide
Pole Configuration	2
Definite Purpose Contactor Contact Current Rating	30 A
Definite Purpose Contactor Contact Arrangement	1 Form X, SPST-NO-DM

Mechanical Attachment

Definite Purpose Contactor Mounting Type	Panel



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2023 (233) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Cadmium oxide (10% in Component Part) Article Safe Usage Statements: Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought





TE Part #2-1609114-1 15CUFS1=F8302



TE Part #1-1437558-1
MTA106DPC=(MSTA) SW TOG P/C TE



TE Part #1-1437597-7
2SWK131AL101=NON UL KEYLOCK
SW





TE Part #6609049-1 3VQ1=F7265 S0



TE Part #2-1393030-9 SSR-480D125=PANEL MNT,125A, 600VAC-DC i/p



TE Part #1924779-1 WIRE DRESS ASSY, 96P GPEC II





Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_6-1393127-9_C.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_6-1393127-9_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_6-1393127-9_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

PRD 10 to 50 Amp Heavy Duty AC or DC Power Relay

English

Product Specifications

Definite Purpose Contactors, 2, 120 VAC Coil Voltage, 30 A, Panel, 1 Form X, SPST-NO-DM, Screw Terminal, 290 Ω Coil Resistance



Definitions General Purpose Relays

English

Agency Approvals

CSA Certificate

English