

SCHRACK | SCHRACK Power PCB Relay RT1

TE Internal #: 6-1393238-0

Power Relays, Standard, Monostable, DC, 400 mW Coil Power Rating DC, 90 Ω Coil Resistance, UL Coil Insulation Class F,

SCHRACK Power PCB Relay RT1

View on TE.com >



Relays, Contactors & Switches > Relays > Power Relays



Power Relay Type: Standard

Coil Magnetic System: Monostable, DC

Coil Power Rating DC: 400 mW

Coil Resistance: 90 Ω

Coil Special Features: UL Coil Insulation Class F

Features

Product Type Features

Power Relay Type	Standard
Electrical Characteristics	
Insulation Initial Dielectric Between Coil & Contact Class	4000 V
Insulation Initial Dielectric Between Open Contacts	1000 Vrms
Contact Limiting Making Current	30 A
Contact Limiting Short-Time Current	16 A
Contact Limiting Continuous Current	16 A
Insulation Creepage Class	8 mm
Coil Power Rating Class	300 – 400 mW
Insulation Initial Dielectric Between Contacts & Coil	5000 Vrms
Insulation Creepage Between Contact & Coil	10 mm[.394 in]
Contact Limiting Breaking Current	16 A
Coil Magnetic System	Monostable, DC
Coil Power Rating DC	400 mW
Coil Resistance	90 Ω
Coil Special Features	UL Coil Insulation Class F
Coil Voltage Rating	6 VDC
Contact Switching Voltage (Max)	400 VAC



Body Features Insulation Special Features Product Weight Contact Features Contact Arrangement Contact Current Class Contact Current Rating (Max)	250 VAC Tracking Index of Relay Base PTI250 14 g[.494 oz] 1 Form C (CO) 10 – 20 A, 16 A 16 A AgNi90/10
Insulation Special Features Product Weight Contact Features Contact Arrangement Contact Current Class	14 g[.494 oz] 1 Form C (CO) 10 – 20 A, 16 A 16 A
Product Weight Contact Features Contact Arrangement Contact Current Class	14 g[.494 oz] 1 Form C (CO) 10 – 20 A, 16 A 16 A
Contact Features Contact Arrangement Contact Current Class	1 Form C (CO) 10 – 20 A, 16 A 16 A
Contact Arrangement Contact Current Class	10 – 20 A, 16 A 16 A
Contact Current Class	10 – 20 A, 16 A 16 A
	16 A
Contact Current Rating (Max)	
	AgNi90/10
Contact Material	
Contact Number of Poles	1
Relay Terminal Type	PCB-THT, Plug-In
Mechanical Attachment	
Relay Mounting Type	Printed Circuit Board, Socket
Dimensions	
Length Class (Mechanical)	25 – 30 mm
Insulation Clearance Class	8 mm
Height Class (Mechanical)	15 – 16 mm
Insulation Clearance Between Contact & Coil	10 mm[.394 in]
Width Class (Mechanical)	12 – 16 mm
Product Width	12.7 mm[.5 in]
Product Length	29 mm[1.142 in]
Product Height	15.7 mm[.618 in]
Usage Conditions	
Environmental Ambient Temperature Class	70 – 85 °C
Environmental Ambient Temperature (Max)	85 °C[185 °F]
Packaging Features	
Packaging Method	Box & Tube, Carton

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU ELV Directive 2000/53/EC Compliant	EU RoHS Directive 2011/65/EU	Compliant
	EU ELV Directive 2000/53/EC	Compliant



China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

















Also in the Series | SCHRACK Power PCB Relay RT1





Customers Also Bought





















Documents

CAD Files

Customer View Model

ENG_CVM_CVM_6-1393238-0_D.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_6-1393238-0_D.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_6-1393238-0_D.2d_dxf.zip

Power Relays, Standard, Monostable, DC, 400 mW Coil Power Rating DC, 90 Ω Coil Resistance, UL Coil Insulation Class F, SCHRACK Power PCB Relay RT1



English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Power PCB Relay RT1

English

Product Specifications

Definitions General Purpose Relays

English

Agency Approvals

VDE Certificate

English