
W92-X1110-10 - ACTIVE

Potter & Brumfield | Potter & Brumfield W9

TE Internal #: 6-1393254-1 Circuit Breakers, Magnetic, Series Trip, Black, Operating Voltage 277 VAC, 10A Current Rating, 2 Pole, Potter & Brumfield W9 View on TE.com >



Relays, Contactors & Switches > Circuit Breakers



Circuit Breaker Type: Magnetic

- Circuit Function: Series Trip
- Illuminated: No
- Actuator Color: Black
- Operating Voltage: 277 VAC

Features

Product Type Features

Illumination Type	No Light
Actuator Type	Toggle
Terminal Configuration	10-32 Stud
Circuit Breaker Type	Magnetic

11	
	luminated

No

\sim	ſ• ,•	F
Con	figuration	Features

	1.52 x 2.065 in
Circuit Function	Series Trip
Number of Poles	2
Electrical Characteristics	
Operating Voltage	277 VAC
Current Rating	10 A
Interrupt Capacity	5000A @ 277VAC
Body Features	
Actuator Color	Black
Contact Features	
Trip Time at 200%	9 – 100 seconds
Mechanical Attachment	

W92-X1110-10

Circuit Breakers, Magnetic, Series Trip, Black, Operating Voltage 277 VAC, 10A Current Rating, 2 Pole, Potter & Brumfield W9



Mounting Options	6-32 Mounting Threads
Dimensions	
Product Height	63.5 mm[2.5 in]
Identification Marking	
Stamped Marking Type	International I/O
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2022 (224) SVHC > Threshold: Cadmium oxide (7.95% in Component part) Article Safe Usage Statements: Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halagan Contant	Not Low Hologon contains $Br \text{ or } Cl > 900$

Not Low Halogen - contains Br or Cl > 900

ppm.

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

W92-X1110-10

Circuit Breakers, Magnetic, Series Trip, Black, Operating Voltage 277 VAC, 10A Current Rating, 2 Pole, Potter & Brumfield W9





Also in the Series | Potter & Brumfield W9



Customers Also Bought



TE Part #5227699-1 BNC PCB VERTICAL	TE Part #2-178128-3 DYNAMIC 3200 REC HSG 3P (SGL)	TE Part #1-111196-9 30 RCPT SYSTEM 50, LEAD FREE	TE Part #3-643817-6 06P MTA156 CONN ASSY 18AWG ORA

	17177777777777777777777777777777777777	Contraction of the second seco	TRANSPORT
TE Part #5650861-5 ASSEMBLY,RECEPTACLE,EUROCARD, T	TE Part #2-111196-6 014 RCPT SYSTEM 50 30 DPLX	TE Part #5206478-3 CLAMSHELL SIZE 3 W/RETAINER	TE Part #207398-6 METRIMATE PIN HEADER ASSY,10P



W92-X1110-10

Circuit Breakers, Magnetic, Series Trip, Black, Operating Voltage 277 VAC, 10A Current Rating, 2 Pole, Potter & Brumfield W9



Documents

CAD Files 3D PDF

3D

Customer View Model

ENG_CVM_CVM_6-1393254-1_E.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_6-1393254-1_E.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_6-1393254-1_E.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages W6/W9 Magnetic Hydraulic Circuit Breaker

English

Agency Approvals UL

English