

Corcom KEM

TE Internal #: 6-1609967-0

3-Phase Filters, 16A Current Rating, Terminal Block Input, Terminal Block Output, DELTA (3 wire + ground), Operating Voltage 520

VAC, Corcom KEM

View on TE.com >



EMI & EMC Solutions > EMI Filters > Power Line Filters > 3-Phase Filters











Current Rating: 16 A

Input Termination Type: Terminal Block
Output Termination Type: Terminal Block
Wiring Configuration: DELTA (3 wire + ground)

Operating Voltage: 520 VAC

Features

Product Type Features

| Filtering Requirements | Filtered |
|--------------------------------------|-------------------------|
| Input Termination Type | Terminal Block |
| Output Termination Type | Terminal Block |
| Configuration Features | |
| Wiring Configuration | DELTA (3 wire + ground) |
| Electrical Characteristics | |
| Leakage Current (Max) (230VAC, 50Hz) | 5 |
| Current Rating | 16 A |
| Operating Voltage | 520 VAC |
| Mechanical Attachment | |
| Product Mount Type | Chassis |
| | |

-25 − 85 °C

Usage Conditions

Operating Temperature Range



Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant with Exemptions |
|-----------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EU ELV Directive 2000/53/EC | Not Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) SVHC > Threshold: Pb (3% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location. |
| Halogen Content | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free |
| Solder Process Capability | Not reviewed for solder process capability |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | Corcom KEM





Customers Also Bought













Documents

Product Drawings

KEM 16A 1S HIGH PER SP BS DELTA 520VAC

English

CAD Files

Customer View Model

ENG_CVM_CVM_6-1609967-0_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_6-1609967-0_B.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_6-1609967-0_B.2d_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

3-Phase Filters, 16A Current Rating, Terminal Block Input, Terminal Block Output, DELTA (3 wire + ground), Operating Voltage 520 VAC, Corcom KEM



Datasheets & Catalog Pages

KEM-BS SERIES

English