

AMP | LEAVYSEAL TE Internal #: 6-1718323-1 Housing for Male Terminals, Wire-to-Wire, 39 Position, .197 in [5 mm] Centerline, Sealable, Brown, Signal, Panel Mount, LEAVYSEAL View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > LEAVYSEAL Housings



Connector System: Wire-to-Wire

Number of Positions: 39

Connector & Housing Type: Housing for Male Terminals

Centerline (Pitch): 5 mm [.197 in]

Sealable: Yes

All LEAVYSEAL Housings (64)



Features

Product Type Features

| Mixed & Hybrid Connector | No | | | |
|------------------------------|----------------------------|--|--|--|
| Connector Shape | Rectangular | | | |
| Connector System | Wire-to-Wire | | | |
| Connector & Housing Type | Housing for Male Terminals | | | |
| Sealable | Yes | | | |
| Primary Locking Feature | On the Terminal | | | |
| Configuration Features | | | | |
| Number of Positions | 39 | | | |
| Number of Rows | 3 | | | |
| Electrical Characteristics | | | | |
| Operating Voltage | 36 VDC | | | |
| Nominal Voltage Architecture | 12 V, 24 V | | | |
| Body Features | | | | |

C For support call+1 800 522 6752

Housing for Male Terminals, Wire-to-Wire, 39 Position, .197 in [5 mm] Centerline, Sealable, Brown, Signal, Panel Mount, LEAVYSEAL



| Cable Exit Angle | 90° | | |
|------------------------------|----------------|--|--|
| Primary Product Color | Brown | | |
| Connector & Keying Code | F | | |
| Contact Features | | | |
| Contact Size | 2.8mm | | |
| Contact Type | Tab | | |
| Mating Tab Width | 2.8 mm[.11 in] | | |
| Contact Current Rating (Max) | 40 A | | |
| Mechanical Attachment | | | |
| Terminal Position Assurance | Yes | | |
| Strain Relief | With | | |
| Mating Alignment Type | Keyed | | |
| Mating Alignment | With | | |
| Connector Mounting Type | Panel Mount | | |
| Housing Features | | | |
| Housing Material | PBT GF | | |
| Centerline (Pitch) | 5 mm[.197 in] | | |

Dimensions

| Connector Height | 45.8 mm[1.803 in] | | | |
|-----------------------------|---|--|--|--|
| Product Width | 70.7 mm[2.783 in] | | | |
| Product Length | 113.25 mm[4.459 in] | | | |
| Row-to-Row Spacing | 5.5 mm[.217 in] | | | |
| Usage Conditions | | | | |
| Operating Temperature (Max) | 70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C[158 °F][167 °F][176 ° F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F] | | | |
| Operating Temperature Range | -40 – 120 °C[-40 – 248 °F] | | | |
| Operation/Application | | | | |
| Circuit Application | Signal | | | |
| Industry Standards | | | | |
| Degree of Protection | IP67, IP69K | | | |
| UL Flammability Rating | UL 94HB | | | |

Housing for Male Terminals, Wire-to-Wire, 39 Position, .197 in [5 mm] Centerline, Sealable, Brown, Signal, Panel Mount, LEAVYSEAL



Packaging Features

| Packaging Quantity | 1 |
|--------------------------------------|---------|
| Packaging Method | Package |
| Other | |
| Serviceable | Yes |
| Connector Position Assurance Capable | No |

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant |
|---|--|
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC |
| Halogen Content | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

Housing for Male Terminals, Wire-to-Wire, 39 Position, .197 in [5 mm] Centerline, Sealable, Brown, Signal, Panel Mount, LEAVYSEAL












Also in the Series LEAVYSEAL



| Automotive | Connector | Caps a | COVCIS | |
|------------|-----------|--------|--------|--|
| (17) | | | | |

Accessories(15)



PCB Headers & Receptacles(16)

Customers Also Bought



Housing for Male Terminals, Wire-to-Wire, 39 Position, .197 in [5 mm] Centerline, Sealable, Brown, Signal, Panel Mount, LEAVYSEAL





Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_6-1718323-1_D_c-6-1718323-1-d.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_6-1718323-1_D_c-6-1718323-1-d.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_6-1718323-1_D_c-6-1718323-1-d.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use

Datasheets & Catalog Pages

ICT Terminals and Connectors Catalogue

English

Product Specifications Application Specification

German