
RLC73K2AR332FTDF <a>Active

CGS | CGS RLC73 TE Internal #: 6-2176571-8 .332 Ω, Thick Film, Current Sensing Resistor, 1 %, 2 Termination, 0805, Taped & Reeled, .125 W, ±200 ppm/°C, Solder, 2 x 1.25 x .55 mm, CGS RLC73

View on TE.com >

Passive Components > Resistors > Surface Mount Resistors



Resistor Type: Current Sensing Resistor

Number of Terminations: 2

Package Size Code: 0805

Packaging Method: Taped & Reeled

Passive Component Tolerance: 1%

Features

E T E connectivity

Product Type Features

| Product Type | Fixed Resistor |
|---|--------------------------|
| Resistor Type | Current Sensing Resistor |
| Package Size Code | 0805 |
| Element Type | Thick Film |
| Configuration Features | |
| Number of Resistors | 1 |
| Electrical Characteristics | |
| Passive Component Tolerance | 1 % |
| Resistance Class | Up to 1kΩ |
| Resistance Value | .332 Ω |
| Power Rating | .125 W |
| Termination Features | |
| Number of Terminations | 2 |
| Surface Mount Resistor Termination Type | Solder |

RLC73K2AR332FTDF

.332 Ω, Thick Film, Current Sensing Resistor, 1 %, 2 Termination, 0805, Taped & Reeled, .125 W, ±200 ppm/°C, Solder, 2 x 1.25 x .55 mm, CGS RLC73



Dimensions

| Passive Component Dimensions | 2 x 1.25 x .55 mm |
|------------------------------|-------------------|
| Usage Conditions | |
| Operating Temperature Range | -55 – 155 °C |
| Temperature Coefficient | ±200 ppm/°C |
| Packaging Features | |
| Packaging Method | Taped & Reeled |
| | |

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant |
|---|--|
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC |

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Halogen Content

Solder Process Capability

Reflow solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts

RLC73K2AR332FTDF

.332 Ω, Thick Film, Current Sensing Resistor, 1 %, 2 Termination, 0805, Taped & Reeled, .125 W, ±200 ppm/°C, Solder, 2 x 1.25 x .55 mm, CGS RLC73





Also in the Series | CGS RLC73



Documents

Product Drawings RLC73K 2A R332 1% 1K RL

English

CAD Files

Customer View Model

ENG_CVM_CVM_6-2176571-8_BA.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_6-2176571-8_BA.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_6-2176571-8_BA.2d_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages SMD Low Ohmic - Current Sense Resistors - Type RLC73 Series

English