TE Internal #: 6-2271110-2

Standard Circular Connectors, Wire-to-Wire / Wire-to-Board, 12 Position, Sealable, Wire & Cable, Signal, Reverse Gender, PA, A

Polarization Code

View on TE.com >



Connectors > Circular Connectors > Standard Circular Connectors











Connector System: Wire-to-Board, Wire-to-Wire

Number of Positions: 12

Sealable: Yes

Connector & Contact Terminates To: Wire & Cable

Circular Connector Insulation Material Type

Contact Current Rating (Max): 1.5 A

Features

Product Type Features

| Product Type | Connector Assembly |
|-----------------------------------|-----------------------------|
| Connector System | Wire-to-Board, Wire-to-Wire |
| Sealable | Yes |
| Connector & Contact Terminates To | Wire & Cable |
| Circular Connector Type | Plug |
| Shell Type | Plastic |
| Configuration Features | |
| Number of Positions | 12 |
| Number of Power Positions | 0 |
| Number of Signal Positions | 12 |
| Contacts Preloaded | Yes |
| Body Features | |
| Shell Base Material | PA |

Polyamide 66 GF25



Contact Features

| Contact reatures | |
|---------------------------------|---------------------------|
| Contact Current Rating (Max) | 1.5 A |
| Reverse Gender | Yes |
| Contact Layout Arrangement | Circular |
| Circular Connector Contact Type | Pin |
| Mechanical Attachment | |
| Polarization Code | A |
| Mating Alignment Type | Keyed |
| Mating Retention | With |
| Housing Features | |
| Circular Connector Shell Size | 12 |
| Dimensions | |
| Wire Size | .25 mm ² |
| Usage Conditions | |
| IP Water Sealing Level | 7 |
| IP Dust Sealing Level | 6 |
| Operating Temperature Range | -40 – 80 °C[-40 – 176 °F] |
| Operation/Application | |
| Circuit Application | Signal |
| Shielded | No |
| Other | |

Product Compliance

Field Serviceable

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant with Exemptions |
|---|---|
| EU ELV Directive 2000/53/EC | Compliant with Exemptions |
| China RoHS 2 Directive MIIT Order No 32, 2016 | Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) SVHC > Threshold: Pb (4% in Component Part) |

Yes



Article Safe Usage Statements:

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

| Halogen Content | Low Halogen - Br, Cl, F, I < 900 ppm per |
|-----------------|--|
| | homogenous material. Also BFR/CFR/PVC |
| | Free |


Solder Process Capability

Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts












Customers Also Bought





















Documents

Product Drawings

M12, MALE, A CODE, 12P, PG9 (AU)

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_6-2271110-2_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_6-2271110-2_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_6-2271110-2_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

Standard Circular Connectors, Wire-to-Wire / Wire-to-Board, 12 Position, Sealable, Wire & Cable, Signal, Reverse Gender, PA, A Polarization Code



M8 / M12 Connector System Catalog

English

M8 / M12 Connector System Catalog

Japanese

Product Specifications

Application Specification

English